(No cember 1983) (No cember 1983) (Fomerly 9: 331) <b>DEPA</b> BU	L TED STATES RTMENT OF THE INTER REAU OF LAND MANAGEMEN	NN Cil Cons. Consiste Concert Construct South of Construct Artesia, NN 88210	• • •	1, 1985 6	
SUNDRY N	IOTICES AND REPORTS proposals to drill or to deepen or plug PLICATION FOR PERMIT for such	ON WELLS	6 IF INDIAN, ALLOTTEE	OR TRIBE NAME	
1 /	7. UNIT AGREEMENT NAME				
CAS WELL OTH 2. NAME OF OPERATOR MCKAY OIL CORPORA 3. ADDRESS OF OPERATOR	JAN 21 1987	Miller Federal			
Post Office Box 2	014, Roswell, New Mexic	d 88241	#4		
<ol> <li>LOCATION OF WELL (Report location clearly and in accordance with any State requirements.<sup>6</sup></li> <li>See also space 17 below.)</li> <li>At surface</li> </ol>			10. FIELD AND POOL OR WILDCAT W. Pecos Slope Abo		
1980' FSL & 1980'	FEL		11. SEC. T., B., M., OR BL SURVEY OF AREA Section 7-6S		
14. PERMIT NO 15 ELEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OR PARISH	13. STATE	
	4203'		Chaves	NM	
16 Chec	k Appropriate Box To Indicate	Nature of Notice, Report, or	Other Data		
NOTICE OF INTENTION TO:		9.085E	SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	BEPAIRING WI		
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTUBE TREATMENT	ALTERING CAS	SING	
SHOOT OR ACIDIZE	ABANDON®	SHOOTING OR ACIDIZING	Surface casing	r•	
REPAIR WELL Other)	CHANGE PLANS	(Other)	ts of multiple completion of pletion Report and Log form	n Well	

17. DESCRIPTION FROM SED OR COMPLETED OF ERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

1-8-87 Spudded  $12\frac{1}{4}$ " hole @ 3 p.m.

1-9-87 Ran in hole w/24 jts., 8 5/8", J-55, 24#, API csg. set @ 1036'. Cemented w/150 sxs. Class "C" cement w/3% CaCl, 150 sxs. Halliburton Lite "C" cmt., w/4% CaCl, plug down @ 8:30 p.m., did not circ. cement. Ran TS, survey indicated TOC @ 750'. Ran in hole w/1" kobe pipe, tagged cement @ 775', brought cement to 610' in 4 stages using 140 sxs. Class "C" w/5% CaCl, 3 yds. pea gravel. Finished bringing cement to surface, a total of 13 stages using 455 sxs. Class "C" w/5% CaCl, 550 gals, flocheck, 13 yds. pea gravel. Job completed @ 3 p.m. 1-10-87.

18. I hereby certify that the foregoing is true and correct				
SIGNED Theresa Rodriguez	TITLE _	Production Analys	t DATE	
(This space for Federal or State office use)	111 1		ACCEPTED FOR RECORD PETER W. CHESTER DATE	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE _			<u> </u>
*0		·	JAN 15 1987	Г
. <b>)e</b> (	e instructi	ions on Reverse Side	BUREAU OF LAND MANAGEMEN	4

Title 15 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to RAS HELETIMENT or agency of the United States any faise, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.