Submit 3 Copies to Appropriate District Office

## State of New Mexico Ene Minerals and Natural Resources Department

Form	C	-1	w	5
Revis	eđ	1.	1	8

P.O. Box 1980, Hobbs, NM &	8Z4(
----------------------------	------

OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO. 3000562372

DISTRICT II		
P.O. Drawer DD, Artesia,	NM	\$8210

Santa Fe, New Mexico 87504-2088

5. Indicate Type of Lease
STATE FEE

DISTRICT III
1000 Rio Brezos Rd., Aztec, NM 87410

6. State Oil & Gas Lance No. LG-5565

SUNDRY NOTICES AND REPO ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL			7. Leass Name or Unit Agreement Name	
( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL DIFFERENT RESERVOIR. USE "APPLI (FORM C-101) FOR SUCH PR	CATION FOR PER	1990 -	INEXCO STATE	
I. Type of Well:  Oil. GAS WELL Y	OTHER C	ARTESIA TOIL		
2. Name of Operator	1000	E17181214510	8. Well No. 7	
McKay Oil Corporation  3. Address of Operator		SI 11 81 81 A	9. Pool name or Wildcat	
P. O. Box 2014, Roswell, NM 88201			W. Pecos Slope ABO	
4. Well Location Unit Letter I : 1980 Feet From The	South	Line and 660	Feet From The East	Line
Section 33 Township 51	S Ran	nge 22E DF, RKB, RT, GR, etc.)	NMFM Chaves	County
\$/////// 410e	6			
11. Check Appropriate Bo	x to Indicate N	Nature of Notice, Re	eport, or Other Data	
NOTICE OF INTENTION TO:		SUB	SEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND A	BANDON X	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON CHANGE PL	ANS	COMMENCE DRILLING	OPNS. PLUG AND ABANDON	MENT 🖳
PULL OR ALTER CASING		CASING TEST AND CE	MENT JOB	
OTHER:		OTHER:	48.	U

12. Describe Proposed or Completed Operations (Clearly state all partinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103.

McKay Oil Corporation plans to plug and Abandon this well as follows:

- i. Set CIBP @ 2921.
- 2. Set 5 sks cement plug 2921' to 2886' approx. 35'.
- 3. POH.
- 4. Cut 4 1/2" @ 2886'.
- 5. Set 25 sks cement plug across 4 1/2" stub 2886' to 2880'.
- 6 WOC
- 7. Set 50 sks cement plug across 8 5/8 shoe 965' to 865'.
- 8. WOC Tag Plug 865'.
- 9. Set 30 sks cement plug 100' to surface.
- 10. Brine gel between all cement plugs. Notify NMOCD to witness plugging operations.
- 11. Install dry hole marker and clear location.

McKay Oil anticipates having this	well plugged and abandoned on or be	fore February 28th, 1999
I hereby certify that the information above is true and complete to a	the best of my knowledge and balled.  TITLE U'CE PRESIDENT	
TYPE OR PRINT NAME		TELEPHONE NO.
(This space for State Use)		1 7 - 44
ATTOMOS MORO STUPPEDEL	TILE Field Reps II	DATE

CONDITIONS OF APPROVAL, IF ANY:

\* Notifie NM OCH. To witness Plugging operations.