

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	✓
FILE	✓
U.S.O.S.	
LAND OFFICE	
OPERATOR	✓

APR -2 1987

O. C. D.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REEVAL OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator McKay Oil Corporation ✓	8. Farm or Lease Name Pipeline Comm.
3. Address of Operator Post Office Box 2014, Roswell, New Mexico 88201	9. Well No. #2
4. Location of Well UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 26 TOWNSHIP 6S RANGE 22E NMPM.	10. Field and Pool, or Wildcat W. Pecos Slope A's
15. Elevation (Show whether DF, RT, GR, etc.) 4244' GL	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Spud, surface & Production csg. ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-3-87 Spudded 12¼" hole @ 6:30 a.m.

3-5-87 Ran in hole w/9 jts. 8 5/8", J-55, 23# casing, set @ 852', cemented w/ 50 sxs Premium Plus w/4% CaCl, 150 sxs. Halliburton Lite w/4% CaCl, 100 sxs. Premium Plus w/2% CaCl. Ran TS, survey indicated TOC @ 650'. Hit bridge @ 280'. Plug #1 set @ 217', cemented w/35 sxs. Premium Plus w/4% CaCl, tagged @ 326; Plug #2 Set @ 280', cemented w/35 sxs Premium Plus w/4% CaCl, tagged @ 248'; Plug #3 set @ 198' w/35 sxs. Premium Plus w/4% CaCl; Plug #4 set @ 197' cemented w/35 sxs. Premium Plus w/4% CaCl + 100 gals. flocheck; Plug #5 set 140' cemented w/35 sxs. Premium Plus w/4% CaCl; Plug #6 set @ 68' cemented w/35 sxs. Premium Plus w/4% CaCl; Plug #7 cemented w/35 sxs, brought cement to surface.

3-14-87 Ran in hole w/78 jts, 4½", 11.6# casing, set @ 3120', cemented w/325 sxs. 65/35 Premium Plus POZ w/2% gel, 4/10th of 1% Halad 4, 3/10th of 1% CFR3, 5# salt, 5# gilsonite, ¼# floseal. Ran 1" pipe from 1400' to surface w/250 sxs. Halliburton Lite Neat.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Theresa RodriguezTITLE Production AnalystDATE 4-1-87Original Signed By
Les A. Clements

APPROVED BY

TITLE

DATE APR 15 1987

CONDITIONS OF APPROVAL, IF ANY:

Supervisor District II

