

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved.
Budget Bureau No. 1004-1
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL

dsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

APR 18 '88

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

McKay Oil Corporation

3. ADDRESS OF OPERATOR

Post Office Box 2014, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below)
At surface

760' FSL & 760' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4336' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Eppers Federal

9. WELL NO.

#3

10. FIELD AND POOL OR WILDCAT

W. Pecos Slope Abo

11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA

Sec. 34-5S-21E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLET

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & Surface csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

3-26-88 Spudded 12 1/4" hole @ 9 p.m.

3-27-88 RIH w/32 jts. 8 5/8", 24# csg. Set @ 912', cemented w/150 sxs. Pacesetter Lite w/3% CaCl, 150 sxs. Calss "C" w/3% CaCl. Plug down @ 7:15 a.m. 3-27-88. Ran temp. survey, survey indicated TOC @ 550'. Ran 1" tubing to 536', cemented to surface w/210 sxs. Class "C" w/5% CaCl in 6 stages. Pressure tested 8 5/8" casing and BOP to 1000 psi. for 30 min. Held ok. WOC 18 hrs.

18. I hereby certify that the foregoing is true and correct

SIGNED Theresa Rodriguez

TITLE Production Analyst

DATE 3-28-88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
BUREAU OF LAND MANAGEMENT
DATE APR 15 1988

APR 15 1988

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side