

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM Oil Cons. Comm. 405
SUBMIT IN 11
Drawer DD
reverse side

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL

NM-32322-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Middle Fork Federal

9. WELL NO.

#3

10. FIELD AND POOL OR WILDCAT

W. Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 8-6S-23E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

McKay Oil Corporation

3. ADDRESS OF OPERATOR

Post Office Box 2014, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

1980' FNL & 1980' FWL

RECEIVED BY

JAN 26 1987

ARTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RI, GR, etc.)

4165' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & Surface Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1-12-87 Spudded 12 1/4" hole @ 10:30 p.m.

1-13-87 Ran in hole w/23 jts. 8 5/8", 32# casing, set @ 924', cemented w/150 sxs. Class "C" cement, 2 1/2% CaCl, plug down @ 2:15 p.m. Ran 1" pipe, cemented w/250 sxs. Premium Plus cement, 4% CaCl, 300 gals. flo check.

Drill cement plug, 2 hrs. circ. plugs, lost circ., out from surface pipe, set 2 @ 150 sxs. Premium Plus cement, w/4% CaCl.

18. I hereby certify that the foregoing is true and correct

SIGNED Cheresa Rodriguez

TITLE Production Analyst

DATE 1-15-87

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER

DATE

JAN 21 1987

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side