

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
NM Oil, Gas, & Geothermal Division  
Artesia, NM 88210

Expires April 1, 1988  
LEASE DESIGNATION AND SERIAL  
NM-36192

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR McKay Oil Corporation	8. FARM OR LEASE NAME Lookout Federal
3. ADDRESS OF OPERATOR Post Office Box 2014, Roswell, New Mexico 88201	9. WELL NO. #9
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 1980' FEL	10. FIELD AND POOL OR WILDCAT W. Pecos Slope Abo
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 9-6S-22E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4356' GL	12. COUNTY OR PARISH Chaves
	13. STATE NM

RECEIVED BY  
MAR -2 1987  
O. C. D.  
ARTESIA OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other) Spud and Surface casing	X
(Other)		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2-5-87 Spudded 12 1/4" hole @ 5 p.m.

2-8-87 Ran in hole w/21 jts. 8 5/8", 24#, J-55 casing, set @ 920'. Cemented w/ 50 sxs. Premium Plus w/4% CaCl, 150 sxs. Premium Plus Howco Lite w/4% CaCl, 100 sxs. Premium Plus w/2% CaCl. Cemented 1" top @ 360', tagged @ 630', set two plugs to circ., cement for a total of 425 sxs. w/4% CaCl and added 200 gals. flocheck. Plug down @ 3:30 a.m.

18. I hereby certify that the foregoing is true and correct

SIGNED Sharon Rodriguez TITLE Production Analyst

DATE 2-10-87

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD  
PETER W. CHESTER  
DATE

FEB 26 1987

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

\*See Instructions on Reverse Side