

U. S. STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Drawer DD

Artesia, NM. 8210-
(Other instructions on re-
verse side)


Form approved.
Budget Bureau No. 1004-01
Expires August 31, 1985

45F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. NAME OF OPERATOR
McClellan Oil Corporation
3. ADDRESS OF OPERATOR
P.O. Drawer 730, Roswell, NM 88202
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface



660' FNL & 1980' FEL

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3764' G.L.

5. LEASE DESIGNATION AND SERIAL NO.
NM-36409
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
MOC Federal
9. WELL NO.
11
10. FIELD AND POOL, OR WILDCAT
Pecos Slope Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28-T5S-R25E
12. COUNTY OR PARISH
Chaves
13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) casing & cement ☐
REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

4/20/87: Set 55' of 14½" conductor. Cemented to surface.

4/27/87: Spudded with 12½" bit.

4/29/87: Set 887' of 8-5/8", 24 lb/ft casing. Cemented with 250 sx of Howco Lite & 200 sx of Class C with 2% CaCl₂. Circulated 100 sx. Plug down at 1:00 pm. Nipple up BOP's. Tested 1000 psi for 30 minutes. WOC - 18 hours. Drill out with 7-7/8" bit.

MAY 3 1987

18. I hereby certify that the foregoing is true and correct

SIGNED Walter Lee

TITLE Drilling Engineer

DATE 5/7/87

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
BETTER W. CHESTER

MAY 18 1987

BUREAU OF LAND MANAGEMENT
ROSOWELL RESOURCE AREA

*See Instructions on Reverse Side