

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input type="checkbox"/>
LAND OFFICE	<input type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

RECEIVED BY  
SANTA FE, NEW MEXICO 87501  
APR 24 1987  
O. C. D.  
ARTESIA, OFFICE  
MAY 11 1987  
O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-78

SUNDARY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO ARTESIA, OFFICE.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator McClellan Oil Corporation 3. Address of Operator P.O. Drawer 730, Roswell, NM 88202 4. Location of Well UNIT LETTER B, 235 FEET FROM THE North LINE AND 1695 FEET FROM THE East LINE, SECTION 1 TOWNSHIP 10-S RANGE 25-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3663' G.L.	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/> 5. State Oil & Gas Lease No. 7. Unit Agreement Name 8. Farm or Lease Name McCrea Com Fee 9. Well No. 2 10. Field and Pool, or Wildcat South Pecos Slope Abo 12. County Chaves
--	--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER Casing & cement ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/17/87: Set 40' of 13-3/8" conductor. Hit water at 30'. Cemented with 125 sx.  
4/19/87: Move in WEK Rig #1.  
4/20/87: Spudded at 4:15 with 12 1/4" bit.  
4/22/87: Drilling at 1090'. Set 1100' of 8-5/8", 24 lb. casing. Cemented with 350 sx Halliburton Lite 2% CaCl and 200 sx Class C 2% CaCl. Circulated 100 sx. WOC. Flange up BOP's & test.  
4/23/87: Drilling out with 7-7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Walter Lee TITLE Drilling Engineer DATE 4/23/87

APPROVED BY Original Signed By  
Los A. Clements TITLE Supervisor District 11 DATE MAY 11 1987

CONDITIONS OF APPROVAL, IF ANY: