

Operator McKay Oil Corporation
 Well Loop - Fork Unit - #2
 Unit M Section 7 Township S Range 22
 API # 30-005-62482

TOPS

140
111
1

← 60' Surface Plug.

Ab. 3100

85' x 956
CIRC

← 1006' Shoe Plug. TAG

← 1500'

Cal T.O.C. 3094'

← 3100'
← 3741' TAG

4 1/2" @ 4325' Perfs. - 3841' - 4184'
w/ 425 SXS mt.

- * Contact OCD 24 hrs. prior to any work done.
- * Salt gel mud consisting of 10# brine with 25# of gel per barrel must be placed between each plug.
- * Install dry hole marker as per Rule 202.B.2
- * Plugs are to be set from point indicated up.
- * Plugs must not be less than 100' or 25 Sacks of cement, whichever is greater, unless specifically indicated.
- * Shoe and stub plugs will be 50' above and below shoe or stub and tagged.
- * Surface plug will be from 0' - 60'
- * Where plugs are required, cement must be placed inside and outside of all casing string(s) in the correct footage or sacks required, if no cement exists.
- * Plugs to be tagged will be indicated.

Call Sherril Bolton @
Agave Energy - 748-4417
with the gas ped. for this
will when the C-104
comes in.

JS