

UNITED STATES

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved  
Budget Bureau No. 1004-011  
Expires August 31, 1985

457

NEW MEXICO DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR McClellan Oil Corporation	8. FARM OR LEASE NAME MM Federal
3. ADDRESS OF OPERATOR P.O. Drawer 730, Roswell, NM 88202	9. WELL NO. 7
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL & 1980' FWL	10. FIELD AND POOL OR WILDCAT Pecos Slope Abo
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25-T9S-R25E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3646' G.L.	12. COUNTY OR PARISH Chaves
	13. STATE NM

RECEIVED BY  
JUL 17 1987  
O. C. D.  
ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other) casing & cement	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6/23/87: Spudded with WEK Rig #1 with 12 1/4" bit.

6/25/87: Ran 930' of 8-5/8", 23 lb casing. Cemented with 250 sx Halliburton Lite, 1/4 lb Flocele, 2% CaCl and 200 sx Class C Premium Plus 2% CaCl. Circulated 50 sx. Nipple up BOP's. Tested 1000 psi for 30 minutes. Drill out with 7-7/8" bit.

BUREAU OF LAND MANAGEMENT  
JUN 30 1987  
ROSWELL NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Match Lee TITLE Drilling Engineer DATE 6/26/87

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
PETER W. CHESTER  
JUL 10 1987  
BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

\*See Instructions on Reverse Side