

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

RECEIVED BY

**AUG 6 - 1987**

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG 4429	

**SUNDRY NOTICES AND REPORT ON WELLS C. D.**  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH ACTIONS.

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name Desert Rose Unit
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1780</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>11</u> TOWNSHIP <u>9S</u> RANGE <u>26E</u> NMPM.		10. Field and Pool, or Wildcat <del>Unit</del> Pecos Slope Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3824' GR		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Spudded 26" hole with Frank's Rathole at 3:30 PM 7-30-87. Set 40' of conductor pipe. Notified Mike Williams, NMOC, Artesia, NM, of spud. Ran 20 joints 8-5/8" 24# J-55 (840.25') casing set 838'. 1-Texas Pattern guide shoe set 838', insert float st 797'. Cemented w/400 sx Pacesetter Lite with 5#/sack Hyseal and 3% CaCl2. (yield 1.98, weight 12.4)'. Tailed in w/200 sx Class "C" with 2% CaCl2 (yield. 1.32, weight 14.8). PD 7:00 PM 8-1-87. Bumped plug to 800 psi, released pressure and float held okay. Cement circulated 38 sacks. WOC. Drilled out 1:00 PM 8-2-87. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Les A. Clements TITLE Production Supervisor DATE 8/3/87

APPROVED BY Original Signed By  
Les A. Clements TITLE Supervisor District II DATE AUG 10 1987

CONDITIONS OF APPROVAL, IF ANY: