STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

ING ESTAMBLES OF TOM	CITAN	1 IAIC
48. 87 COPIES SECEIVES		
DISTRIBUTION		
SANTA FE		
FILE		1
U.S.G.S.		
LAND OFFICE		

OIL CONSERVATION DIVISIONED	Sam C 102
P. O. BOX 2088 SANTA FE SANTA FE, NEW MEXICO 87501	Form C-103 - Revised 10-1-73
U.S.G.S. SEP 04 187	Sa. Indicate Type of Lease State X Fee
OPERATOR O. C. D.	5. State Oil & Gas Lease No. LG 4429
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUE BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM SUCH POR SUCH PROPOSALS.)	
1. OIL GAS X OTHER-	7. Unit Agreement Name Desert Rose Unit
2. Name of Operator	8. Farm or Lease Name
Yates Petroleum Corporation J. Address of Operator	9. Weil No.
105 South 4th St., Artesia, NM 88210	1
4. Location of Well UNIT LETTER H 1780 FEET FROM THE NORTH LINE AND 660 FEET FROM	10. Field and Pool, or Wildcat Und. Pecos Slope Abo
THE EAST LINE, SECTION 11 TOWNSHIP 9S RANGE 26E NMPM	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3824' GR	Chaves ()
Check Appropriate Box To Indicate Nature of Notice, Report or Ot NOTICE OF INTENTION TO: SUBSEQUENT	her Data T REPORT OF:
NOTICE OF INTENTION TO.	- 112. 011. 01.
PERFORM REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	PLUG AND ASANDONMENT
OTHER Production Casin	ng, Perforate, Treat X
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703.	s estimated date of starting any proposed
TD 6360'. Reached TD 1:45 AM 8-20-87. Ran 154 joints 5-1/2" 15.5# J-55 casing set 6360'. Regular guide float collar set 6322'. Cemented w/275 sacks 65/35 Poz "C" with 5 Halad-4, .3% CFR-3 and 1/4#/sack floseal (Yield 1.4, weight 14.1). Bumped plug to 2000 psi, released pressure, float and casing held 9-1-87. WIH and perforated 14 .42" holes as follows: 6272-76' (293, 94, 95, 99, 6300' (1 SPF-6 holes). Treated perforations 6272-	5#/salt, .4% PD 3:30 PM 8-22-87. okay. 2 SPF-8 holes), 6292,
with 2500 gals 7-1/2% NEFE acid and ball sealers.	(14 holes)
•	
is. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Production Supervisor	DATE 9/3/87
Original Signed By	
Les A. Clam, en	SEP 1 0 1987
Supervisor District (1	