

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

MAR 09 '88

O.C.D.
ARTESIA OFFICE

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER		7. Unit Agreement Name
2. Name of Operator McKay Oil Corporation		8. Farm or Lease Name Homestead
3. Address of Operator Post Office Box 2014, Roswell, NM 88201		9. Well No. #1
4. Location of Well UNIT LETTER <u>J</u> <u>1676</u> FEET FROM THE <u>East</u> LINE AND <u>1676</u> FEET FROM THE <u>South</u> LINE, SECTION <u>20</u> TOWNSHIP <u>6S</u> RANGE <u>22E</u> NMPM.		10. Field and Pool, or Wildcat W. Pecos Slope Abo
11. Elevation (Show whether DF, RT, GR, etc.) 4278' GR		12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER <u>Surface & Production csg.</u> ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-26-88 RIH w/23 jts. 8 5/8" csg., LS R3, 24#, (855'), set @ 863', cemented w/50 sxs. Class "C" plus 5# Hi-seal per sx. & 1/2# cello seal w/4% CaCl, 150 sxs. Pacesetter Lite "C" w/4% CaCl, 100 sxs. Calss "C" w/3% CaCl. 1" cemented w/35 sxs. Class "C" w/9% CaCl. Ran TS, survey indicated TOC @ 200'. 100' cmt'd w/35 sxs. Class "C" w/9% CaCl, tagged @ 60' w/35 sxs. cement 9% CaCl, Tagged 30' 35 sxs. cement circ. to surface. Plug down @ 9:30 p.m.

3-7-88 Ran in hole w/81 jts. 4 1/2" csg. (3253') set @ 3251'. Cemented w/325 sxs. cement. Plug down @ 2:36 a.m. 100 18 hr. psi 1000#.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Theresa Rodriguez TITLE Production Analyst DATE 3-8-88
Original Signed By Mike Williams
APPROVED BY Oil & Gas Inspector TITLE DATE MAR 31 1988
CONDITIONS OF APPROVAL, IF ANY: