

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	☒
LAND OFFICE	☒
OPERATOR	☒

DEC 15 '88

O. C. D.

LAND OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Plains Radio & Broadcasting ☒

Address of Operator

P.O. Box 1393, Roswell, NM 88202

Location of Well

UNIT LETTER H 1980 FEET FROM THE N 660 FEET FROM

THE East 7 LINE, SECTION 9S 27E TOWNSHIP 27E RANGE 27E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3864 GR

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

L 5441

7. Unit Agreement Name

8. Farm or Lease Name

Camel State

9. Well No.

#3

10. Field and Pool, or Wildcat

Foor Ranch Pre-Permian

12. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

FORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PLUG OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☒

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Set CIBP at 6150 with 35 ft. cement on top.
2. Set 100' cement plug inside 5½" casing at 5300', top of wolfcamp.
3. Set 100' cement plug inside 5½" casing at 4600', top of ABO.
4. Shoot off casing at 4000' ±, depending on free point, and recover 4000' of 5½" casing.
5. TIH with tubing and spct 100' cement plug accross stub of 5½" casing, 50' in and 50' out.
6. ** Spot 100' cement @ 2500' Top of Glorieta*
Spot 100' cement plug accross shoe of 8 5/8" casing, 50' in and 50' out.
7. Spot 50' plug at surface.
8. Install regulation dry hole marker.

Note: all cement plugs will be class "C".

** Gel between plugs*

25% minimum plug

Notify N.M.O.C.C. in sufficient time to wire

Plugging

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

BY John T. Pool
** Note as above*

TITLE Inspector

DATE 12-17-88

APPROVED BY Johnny Robinson
ADDITIONAL APPROVAL, IF ANY:

TITLE Oil & Gas Inspector

DATE 12-21-88