

UN ED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NM Oil Cons. Commission
Drawer DD
SUBMIT IN TRI ATE*
(Other In 88610 on re-
verse side)
RECEIVED

Form approved.
Budget Bureau No. 1004-011
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-8431

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Penjack Fed.

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6-T10S-R26E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

SEP 30 87

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. NAME OF OPERATOR
McClellan Oil Corporation ✓
3. ADDRESS OF OPERATOR
P.O. Drawer 730, Roswell, NM 88202
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & 1650' FWL

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3732' G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) 8-5/8" casing

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9/21/87: Move in WEK Rig 1. Spud with 12 1/4" bit.

9/24/87: Ran 1095' (24 joints) of 8-5/8", 23 lb casing. Cemented using Halliburton with 350 sx Halliburton Lite 1/4 lb Flocele, 2% CaCl & 200 sx of Premium Plus cement, 2% CaCl. Circulated 43 sx.

9/25/87: Nipple up BOP & test 1000 psi for 30 minutes. Drill out with 7-7/8" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark Lee TITLE Drilling Engineer

DATE 9/25/87

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

