

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

JAN 26 '88

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

105 South 4th st., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FNL & 660' FEL

14. PERMIT NO.

API #30-005-62576

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3861' GR

6. IF INDIAN, ALLOTTEE OR TRIBE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Engwall RL Federal

9. WELL NO.

2

10. FIELD AND POOL OR WILDCAT

2. Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit H, Sec. 4-T9S-R26E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Set production csg, perforate

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 5050'. Reached TD 10:45 AM 1-11-88.

Ran 121 joints 4-1/2" casing 9.5# J-55 set 5050'. Guide shoe set 5050', float collar set 5008'. Cemented w/475 sx 65/35 Poz + 5#/sx Salt, .4% Halad, .3% CFR-3 and 1/4#/sx Flocele (yield 1.41, weight 14.0). PD 5:00 PM 1-12-88. Bumped plug to 1300 psi, held okay. WOC 18 hrs. Ran 1500' of 1". Cemented w/300 sx Pacesetter Lite. Perforated 25 .42" holes as follows; 4443, 44, 45, 46, 51, 52, 53, 54, 55, 56' (10 holes), 4780, 81, 82, 83, 85, 86, 87, 88' (8 holes), 4813-17' (7 holes). Acidized perforations 4813-17' and 4780-88' w/2000 gals 7 1/2% acid. Acidized perforations 4443-56' w/1000 gals 7 1/2% acid and ball sealers. Frac'd perforations 4443-4817' (25 holes) w/80000 gals gel 2% KCL water and 120000# 20/40 sand.

18. I hereby certify that the foregoing is true and correct

SIGNED *Peter W. Chester*

TITLE Production Supervisor

DATE 1-20-88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE

JAN 22 1988

BUREAU OF LAND MANAGEMENT
ROSSELL RESOURCE AREA

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.