

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

Form O-101
Revised 11-1-77

NO. OF COPIES FILED	
DATE	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

DEC 30 '87

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> For <input type="checkbox"/>
5. State Oil & Gas Lease No. L-3086

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM O-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Erickson KY State
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Well No. 2
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>2</u> TOWNSHIP <u>10S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat South Pecos Slope Abo
11. Elevation (Show whether DF, RT, GR, etc.) 3635.4' GR	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 1:50 PM 12-20-87 with Frank's Rathole. Set 40' of 20" conductor. Notified Darrell Moore, NMOC, Artesia, NM, of spud. Resumed drilling 12-1/4" hole with rotary tool 4:30 PM 12-22-87.

Ran 24 joints 8-5/8" 24# J-55 casing set 1005'. Guide shoe set 1005', insert float set 963'. Cemented w/400 sx Pacesetter Lite with 1/4#/sx Celloseal + 3% CaCl (yield 1.81, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (Yield 1.32, weight 14.8). PD 12:30 PM 12-24-87. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 50 sx to pit. WOC. Drilled out 7:00 PM 12-26-87. WOC 30 hrs and 30 minutes (shut down for Christmas). NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Mike Williams TITLE Production Supervisor DATE 12-28-87

Original Signed By Mike Williams TITLE Oil & Gas Inspector DATE JAN 05 1988

CONDITIONS OF APPROVAL, IF ANY: