

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Anhy 200
Salt
Salt
Yates 234
7 Rivers 330
Queen 840
Grayburg
San Andres 1325
Glorieta
Paddock
Blinbry
Tubb 3970
Drinkard
Abo 4716
Wolfcamp 5472
Penn 6100
Cisco (Bough C)

T. Canyon
T. Strawn
T. Atoka
T. Miss
T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Delaware Sand
T. Bone Springs
T.
T.
T.

Northwestern New Mexico

T. Ojo Alamo
T. Kirtland-Fruitland
T. Pictured Cliffs
T. Cliff House
T. Menefee
T. Point Lookout
T. Mancos
T. Gallup
Base Greenhorn
T. Dakota
T. Morrison
T. Todilto
T. Entrada
T. Wingate
T. Chinle
T. Permian
T. Penn "A"

T. Penn. "B"
T. Penn. "C"
T. Penn. "D"
T. Leadville
T. Madison
T. Elbert
T. McCracken
T. Ignacio Otzte
T. Granite
T.
T.
T.
T.
T.
T.
T.

OIL OR GAS SANDS OR ZONES

No. 1, from 5104 to 5114 (GAS)
No. 2, from 6214 to 6281 (GAS)
No. 3, from to
No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from NONE to feet
No. 2, from to feet
No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	200	200	Red Bed				
200	234	34	Anhydrite				
234	330	96	Sady Shale				
330	840	510	Red Shale & Anhydrite				
840	1235	485	Red Sand				
1235	3970	2645	Lime and Anhydrite				
3970	4716	746	Dolomite, Lime and Anhy.				
4716	5472	756	Red ABO Shale w/ Sand Stringers.				
5472	6520	1048	Sand, Shale & Dolomite				