

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

EP

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-62589

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

McConkey HX

7. Well No.

#4

8. Pool name or Wildcat

**Undesignated Foor Ranch
Pre-Permian**

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter **L** : **1980** feet from the **South** line and **660** feet from the **West** line

Section **10** Township **9S** Range **26E** NMPM **Chaves** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3813' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/26/00 - RU rotary tools. Resume drilling at 5:00 PM. Drilled out cement plug 75-102'.

9/27 - 10/1/00 - Drilled out cement plugs to previous TD of 5020'.

10/2/00 - Began drilling new formation at 2:30 AM.

10/9/00 - Reached TD at 6480' at 1:30 PM.

10/11/00 - Logging well. Logger's TD 6468'.

10/13/00 - Ran 153 jts. (6481.25') casing set at 6480' as follows:

56 jts. (2348.27') 5-1/2" 15.5# 8R J55 SB 97 jts. (4132.98') 5-1/2" 15.5# 8R J55 Varn

Float shoe set at 6480'. Float collar set at 6438.24'. Bottom marker set at 4131.73'.

Cemented with 600 sxs Pecos Valley Lite + 1 pps D44, 4 pps D42, .2% D65, .3% D167, .2% D46, .15% d13 (yld 1.42, wt 13). PD at 4:45 PM. Bumped plug to 1800 psi for 2 mins. Held OK

Notified Artesia OCD Mike Stubblefield of operations.

Released rig at 8:45 PM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE **Engineering Technician** DATE **September 14, 2001**

Type or print name **Susan Herpin**

Telephone No. **505-748-1471**

(This space for State use) **ORIGINAL SIGNED BY TIM W. GUM**

DISTRICT II SUPERVISOR

APPROVED BY [Signature] TITLE _____ DATE **SEP 18 2001**

Conditions of approval, if any: