

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2083
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

FEB 24 '88

O. C. D.

ARTESIA, OFFICE

5a. Indicate Type of Lease	
State ☒	For ☐
5. State Oil & Gas Lease No.	
LG 4429	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-	7. Unit Agreement Name Desert Rose Unit
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Desert Rose Unit
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Well No. 3
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>11</u> TOWNSHIP <u>9S</u> RANGE <u>26E</u> NMPM.	10. Field and Pool, or Wildcat South Pecos Slope Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3840.6' GR	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 12:15 PM 2-19-88. Set 40' of 20" conductor pipe.. Redi-mix to surface. Notified Darrell Moore, NMOCD, Artesia, NM, of spud. Resumed drilling 12-1/4" hole 12:00 AM 2-22-88. Ran 27 joints 8-5/8" 24# J-55 casing, set 1125'. Guide shoe set 1125', insert float set 1093'. Cemented w/425 sx Pacesetter Lite "C" + 1/4#/sx Celloseal + 3#/sx gilsonite + 3% CaCl (yield 1.98, weight 12.4). Tailed in w/150 sx Class "C" with 2% CaCl (yield 1.32, weight 14.8). PD 7:45 AM 2-23-88. Bumped plug to 800 psi, released pressure and float held okay. Cement circulated 50 sacks to surface. WOC. Drilled out 12:45 AM 2-24-88. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed <u>Mike Williams</u>	TITLE <u>Production Supervisor</u>	DATE <u>2-24-88</u>
Original Signed By Mike Williams		MAR 7 1988
APPROVED BY <u>Oil & Gas Inspector</u>	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		