STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

we. or Corice Receives	1	
DISTRIBUTION		
SANTA FE		V
FILE		
U.1.0.1.		
LAND OFFICE		/
OPERATOR	17	

OIL CONSERVATION DIVISION

DISTRIBUTION	P. O. BO	X 2088	Revised 10-1-78	
SANTA FE	SANTA FE, NEW	MEXICO 87501	*	
rice		•	Sa, Indicate Type of Lease	
U.3.0.3.	4	RECEIVED	State X Fee	
LAND OFFICE	. ·		5, State Oil & Gas Lease No.	
OPERATOR /			LG-9805	
		1iu 1 ♥ '00	mmmmmk	
SUNDR	RY NOTICES AND REPORTS ON	WELLS JUL 18 '88		
	ION FOR PEHMIT -" (FORM C-101) FOR SUC	H PROPOSALS.)	VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	
1. 611 649 [翌]		O. C. D.	7. Unit Agreement Name	
OIL WELL X	OTHER-	ARTESIA, OFFICE		
2. Name of Operator			8, Farm or Lease Name	
Yates Petroleum Com	rporation V	·	Enron AEY State	
3. Address of Operator			9. Well No.	
105 South 4th St.,	Artesia, NM 88210		1	
4. Location of Well			10. Field and Pool, or Wildcat	
K .	1980 FEET FROM THE South	1980	Wildcat OR DOVICIA	
UNIT LETTER	FEET FROM THE	LINE AND PEET PROM		
West	25 99	26E		
THE WEST LINE, SECTI	ON 25 TOWNSHIP 9S	RANGE ZOE NMPM		
THITTHING THE	15. Elevation (Show whether	DF. RT. GR. etc.)	12. County	
		3810.6' GR	Chaves	
		3010:0 GK	- suaves	
Check	Appropriate Box To Indicate N	lature of Notice, Report or Ot	her Data	
NOTICE OF I	NTENTION TO:	SUBSEQUEN'	T REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ASANDON		COMMENCE DRILLING OPNS.	PLUG AND ASANDONMENT	
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOS X		
POLE ON ALTER CASING		отнея		
	. \square			
OTHER				
17. Describe Proposed or Completed O	perations (Clearly state all pertinent det	ails, and give pertinent dates, including	estimated date of starting any proposed	
work) SEE RULE 1103.	•			
Spudded 26" hole 11	1:00 AM 7-10-88. Set 40'	of 20" conductor pipe.	Resumed drilling	
12-1/4" hole 6:15 PM 7-11-88. Notified NMOCD, Artesia, NM. Lost returns at 136'.				
Mix LCM mud.				
Ran 28 joints 8-5/8" 24# ST&C casing set 1198'. Texas Pattern notched guide shoe set				
1198', insert float set 1155'. Cemented w/425 sx Pacesetter Lite w/1/4#/sx Celloseal,				
3#/sy gilsonite and	d 37 CaC12 (viold 1 98 to	oight 12 /) Toiled in	71/4#/SX CETTOSEAT;	
3#/sx gilsonite and $3%$ CaCl2 (yield 1.98, weight 12.4). Tailed in $#/250$ sx Class "C" with $2%$ CaCl (yield 1.33, weight 14.8). PD 3:07 AM 7-13-88. Bumped plug to 800 psi,				
float held okay. Cement circulated 50 sacks. WOC.				
Drilled out 1:15 AM 7-14-88. WOC 22 hrs and 8 minutes. NU and tested to 800 psi, OK.				
Reduced hole to /-/	7/8". Resumed drilling.			
	•			
,	•			
	•		•	
•				
10 Thereby and for the Information	above is true and complete to the beat	of my knowledge and belief		
18. I beleat centily that the information	. moore is true and complete to the Deat (or mit amounted and periets		
()			- - /	
or and	as alex TITLE P	Production Supervisor	DATE 7-14-88	
-/-				
Original Signed			.1111 1 9 1088	