STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

THO I AND IVITIVE CORE TON		
40. 00 (00160 06661460		
DISTRIBUTION		<u> </u>
SANTA FE	V	
FILE	V	V
U.1.0.1.		
LAND OFFICE		<u> </u>
OPERATOR	$\Box Z$	1

ue, er corico acceives	OIL CONSERVAT	TION DIVISION			
	P. O. BOX	2088 RECEIVED	Form C-103 · Revised 10-1-78		
SANTA FE	SANTA FE, NEW		API #30-005-62599		
	SANTA L, NEW		Sa. Indicate Type of Lease		
V.S.G.S.		MAD OF 100	State XX Fee		
LAND OFFICE		MAR 28 '88	5. State Oil & Gas Lease No.		
OPERATOR	·		LG 939		
		0.00	TG 333		
SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE (DO NOT USE THIS FORM FOR PROPOSALS TO DELLE ON TO DECERN OR PLUG BACK TO A DIFFERENT RESERVOIR.					
1.			7, Unit Agreement Name		
AU (SAS (V)	THER-	· · · · · · · · · · · · · · · · · · ·			
2. Name of Operator			8. Farm or Lease Nume		
Yates Petroleum Corporation V		Witz VN State			
			9. Well No.		
1. Address of Operator 105 South 4th St., Artesia, NM 88210		2			
			10. Field and Pool, or Wildcat		
4. Location of Well	•		Wildcat Penn		
UNIT LETTER A 660	FEET FROM THE North	LINE AND <u>660</u> FEET FROM			
ì		0/7			
THE East LINE, SECTION	26 TOWNSHIP 98	HANGE HMPM			
			12. County		
15. Elevation (Show whether DF, RT, GR, etc.)		1 /////////			
3802.7' GR			Chaves		
16. Check Appr	consiste Box To Indicate N	ature of Notice, Report or O	ther Data		
NOTICE OF INTE		SUBSEQUEN	T REPORT OF:		
NOTICE OF INTE	111014 10:				
	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING		
PERFORM REMEDIAL WORK	PEGG X40 X2X4004	COMMENCE DRILLING OPHS.	FLUG AND ABANDONMENT		
TEMPORARILY ABANDON		CASING TEST AND CEMENT JOB			
PULL OR ALTER CASING	CHANGE PLANS				
·	l	OTHER			
OTHER					
17, Describe Proposed or Completed Operati	(Clearly state all pertinent deta	uls and sive pertinent dates, includin	g estimated date of starting any proposed		
17. Describe Proposed or Completed Operation (work) SEE RULE 1103.	one (Creamy store and permitted	,			
•		2011 conductor nine N	otified Mike		
Spudded 26" hole 8:45 Pl		zo conductor prpe. N	Office Hive		
Williams, NMOCD, Artesia	a, NM, of spud.	0.5/01/0/	# 7 55		
Resumed drilling 12-1/4	" hole 2:15 PM 3-22-88	. Ran 24 jts 8-5/8" 24	# J-55 casing set		
10001 Maria Dattoma N	stabed audde choe set	1009', insert float set	967'. Cemented		

1009'. Texas Pattern Notched guide shoe set 1009', insert float w/400 sx Pacesetter Lite w/1/4#/sx Celloseal + 3% CaCl (yield 1.81, weight 12.6). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, weight 14.8). PD 6:45 PM 3-23-88. Bumped plug to 400 psi, released pressure and float held okay. Cement circulated 69 sx to pit. WOC. Drilled out 1:00 PM 3-24-88. WOC 18 hrs, 15 mins. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

(),	information above is true and complete	to the b	Production Supervisor	DATE_	3-25-88
APPROVED BY	Original Signed By Mike Williams			DAYE	MAR 2 9 1988