Form 3160-5 (November 1983)	UN STAT	ES NM	SUBMIT IN TRIP	- ist	Budget Bureau N Expires August  5. LEASE DESIGNATION	
(Formerly 9-331) <b>DEI</b>	BUREAU OF LAND MAN	AGEMENT	peria, NM 88	8210	NM 374	
SUNDRY	NOTICES AND REI	PORTS ON	WELLS	ir.	6. IF INDIAN, ALLOTTEE	
1.	AFFERNATION TO TELEPONE	RECEIVE	D BY		7. UNIT AGREEMENT NA	KE .
OIL GAS WELL X	OTHER	MAR -5	1985		8. FARM OR LEASE NAM	E .
Yates Petroleum	Corporation				Asparas ABX Fe	deral
3. ADDRESS OF OPERATOR		O. C			9. WBLL NO.	
207 South 4th St	., Artesia, NM 882	10 ARTESIA,	requirements.*		10. FIELD AND POOL, OR	WILDCAT
See also space 17 below.) At surface					Wildcat-abo	
790 FNL & 1980 FWL, Sec. 21-T4S-R16E					11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
					Unit C, Sec. 21-T4S-R16E	
14. PERMIT NO.	14. PERMIT NO. 15. ELEVATIONS (Show whether DF,				12. COUNTY OR PARISH 13. STATE	
	56	35' GR			Lincoln	NM
13. <b>Ch</b>	eck Appropriate Box To	Indicate Nature	of Notice, Rep	ort, or O	ther Data	
•• •					UENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASINO	, 🔲	WATER SHUT-OFF	X	REPAIRING W	FELL
FRACTURE TREAT	MULTIPLE COMPLETE		FRACTURE TREATM	ENT _	ALTEBING CA	BING
SHOOT OB ACIDIZE	ABANDON*		SHOOTING OR ACID	IZING	ABANDONMEN	
REPAIR WELL (Other)	CHANGE PLANS		(Other) (Note: Repo	ort results	of multiple completion of tion Report and Log for	on Well
17. DESCRIBE PROPOSED OR COMPI proposed work. If well	ETED OPERATIONS (Clearly stat is directionally drilled, give su	e all pertinent deta bsurface locations a				
Plug set 39. Plug #3: Tagged cemer Plug set 39. out 2:30 PM Set lost cir Plug #4: Spotted 100 2-18-85. Plug #5: Tagged cemer	ride shoe set 218'.  1/2#/sx cellosea.  Compressive striction, released pressure.  18 hrs and 15 minster.  Drilled plug and irculation plugs as C 4% CaCl2. PD and at 395'. Spotter.  WOC 1 hour.  2-17-85. Drilled reculation plugs as sx Class C, 10#/structulation plugs as sx Class C, 10#/structulation plugs as Loaded hole and regoing to true and correct	Insert fill and 3% Cacrength of	loat set 176 C12. Tailed ement-1150 p ay. Cement tested to 10 rilling. Lo 7-185. Plug lass C 4% Ca nt at 245'. t circulatio 1#/sx cellos lass C, 10#/ at 350'. W lled out 12:	in w/15 si in 1 circula 000 psi est circ 3 set 39 aC12. PI aC12. I Loaded on at 39 seal and seal and seal and seal and	mented w/250 sz 50 sx Class C v 12 hrs. PD 6:30 ated 50 sx. Dr for 30 minutes culation at 320 95'. WOC 1 how 0 4:15 AM 2-17-17-17-17-18-18-18-18-18-18-18-18-18-18-18-18-18-	R Pacesetter  8/1/4#/sx  15 PM 2-15-85.  rilled out  6, OK. Re-  10'. Pumped  11.  12.15 AM  11.  11.  11.  12.15 AM
SIGNED Janu	/5	TITLE Produ	ction Superv	/1sor	DATE	0-83
(This space for Federal or	ACCEPTED FOR RECORD			A.		
APPROVED BYCONDITIONS OF APPROV	PETER W. CHESTER	TITLE		,	DATE	
	MAR 1 1985, See	Instructions on	Reverse Side	r.		
Title 18 U.S.C. Section 100 United States any false fie	REAU OF LAND MANAGEN RORAMSLIRESOURGERANT	MENT	ly and willfully to	o make to matter wi	any department or a thin its jurisdiction.	gency of the