

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

*Copy to 5r*

5. LEASE DESIGNATION AND SERIAL NO.

USA N. M. - 9742

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-----

7. UNIT AGREEMENT NAME

Jornada del Muerto

8. FARM OR LEASE NAME

Jornada del Muerto

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

22-13S-1E

1.

OIL WELL  GAS WELL  OTHER  Dry Hole

2. NAME OF OPERATOR

BEARD OIL COMPANY

3. ADDRESS OF OPERATOR

2000 Classen Center, Suite 200 South,  
Oklahoma City, Oklahoma 73106

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)  
At surface

827' FSL & 2197' FWL of Section 22-13S-1E  
Sierra County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5468' GL; 5479' KB

12. COUNTY OR PARISH

Sierra

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well was spudded March 4, 1975. 8-5/8", 28# casing was set @ 416' w/340 sks cement. Cement circulated. Well was drilled to 2325' TD. No drill stem tests or cores were taken. Verbal permission to plug was obtained from Mr. James A. Knauf, District Engineer, U. S. G. S, Artesia, New Mexico, with cement plugs to be set as noted below:

50 sks from 2325-2175'

50 sks from 1480-1330'

35 sks from 430- 330'

5 sks from 40- 20'

3 sks in top of surface casing w/a regulation dry hole marker placed in top of surface casing and extending 4' above ground level.

RECEIVED

APR 9 1975

O. C. C.  
ARTESIA, OFFICE

RECEIVED

MAR 20 1975

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*James W. Vater, Jr.*  
James W. Vater, Jr.

TITLE Operations Manager

DATE 3-18-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*[Signature]*

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.