

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

| | | | | | |
|---|--|---|-------------------------------------|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | <input checked="" type="checkbox"/> | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF PLUGGING WELL | | REPORT ON RECOMPLETION OPERATION | | REPORT ON (Other) | |

January 26, 1953

(Date)

Maljamar, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Kewanee Oil Company

(Company or Operator)

F-M Unit

(Lease)

Kincaid & Watson

(Contractor)

Well No. 1 in the SE 1/4 SW 1/4 of Sec. 26

T. 18S, R. 18E, NMPM, Wildcat Pool, Chaves County.

The Dates of this work were as follows: January 9, 1953 and January 12, 1953.

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan (was) (~~was not~~) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On January 9, 1953 ran 37 joints of 10-3/4" OD - 40.5# - J55 - Rge 2 - 8 rd thd - S T&C - Regular - SS - New Casing and set @ 1147' 5" (ground level). Cemented with 180 sacks of neat cement & 3 sacks of Calcium Chloride. On January 12, 1953 pumped 35 sacks of cement behind casing and then set a bridge outside casing at 60' with rock & mud. Then mixed 5 sacks of calseal & poured on top of bridge. Let calseal set 1 hour. Then pumped in 115 sacks of cement and 2 sacks of calcium chloride and cement filled up 30' in hole. Then pumped in 200 sacks of cement & 13 sacks of calcium chloride (Pumped in 100 sacks & let well set 15 minutes to check fillup and then pumped in other 100 sacks) and cement filled up to bottom of cellar. All work done by Halliburton Oil Well Cementing Company. Let well stand for cement to set.

Started up on January 22, 1953 with rotary tools and tested casing to 300# pressure.

Witnessed by R. A. McGill Kewanee Oil Company District Superintendent
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name R. A. McGill

Position District Superintendent

Representing Kewanee Oil Company

Address P. O. Box 124, Maljamar, New Mexico

OIL AND GAS INSPECTOR

(Title)

JAN 30 1953

(Date)