

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

May 23, 1953

(Date)

Maljamar, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Kewanee Oil Company

(Company or Operator)

P-M Unit

(Lease)

Kincaid & Watson

(Contractor)

Well No. 1 in the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of Sec. 26T. 18S, R. 18E, NMPM., Wildcat Pool, Chaves County.The Dates of this work were as follows: May 2, 1953 to May 16, 1953Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____,

(Cross out incorrect words)

and approval of the proposed plan (was) (~~was not~~) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On May 2, 1953 set Lane-Wells Wire Line Bridging Plug @ 6436' ground level. On May 3, 1953 ran tubing in hole and spotted cement plug from 6436' to 6336' with 20 sacks of common cement. Loaded hole with mud and pulled tubing out of hole. On May 5, 1953 ran McGullough Magna-Tector. Found pipe freeze @ 1200'. Then cut 7" casing off @ 4979' with Jet Cutter. Circulated oil in hole and let well set. Moved in well plugging unit on May 12, 1953 and started pipe out of hole. Pulled 4979' of 7" casing out of hole. Ran tubing back in hole to 4979' and filled hole with mud. Circulated oil back out of hole. Set cement plug at 4979' with 10 sacks of common cement. Pulled tubing up to 1157' and spotted 10 sacks of common cement from 1157' to 1137'. Then pulled tubing up to 1095', flushed hole with clear water and then pulled tubing out of hole. Ran tubing back in hole with 10-3/4" Baker bridging plug and set @ 1086' and spotted 10 sacks of cement on top of plug. Top of cement at approximately 1066'. Then pulled tubing out of hole. Set a marker of 4" pipe at well.

Well was plugged and abandoned on May 16, 1953.

Confirming conversation with Mr. L. A. Hansen.

Witnessed by R. A. McGill

(Name)

Kewanee Oil Company


(Company)

District Superintendent

(Title)

Approved:

OIL CONSERVATION COMMISSION



(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name R. A. McGillPosition District SuperintendentRepresenting Kewanee Oil CompanyAddress P. O. Box 124, Maljamar, New Mexico

(Title)

(Date)