

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

DUPLICATE

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL XX	

Albuquerque, New Mexico

November 16, 1939

Place

Date

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico.

Gentlemen:

330 / NEW

Following is a report on the work done and the results obtained under the heading noted above at the

E. J. Fisher Foster Well No. 1 in the
Company or Operator Lease
NW 1/4 of the NW 1/4 of Sec. 7, T. 15 South, R. 26 East, N. M. P. M.,
Wildcat Field, Chaves County

The dates of this work were as follows: October 29, 1939 to November 4, 1939

Notice of intention to do the work was ~~was not~~ submitted on Form C-102 on August 23 1939
and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Filled with heavy mud from 1281' to 1240', bridged and cemented with ten (10) sacks of cement at 1240'. Then filled with heavy mud to 1309', bridged and cemented with ten (10) sacks of cement at 1309' through the bottom of the water rock. Then filled with mud to 100', cemented with ten (10) sacks. Then filled with mud to bottom of cellar and cemented regulation marker. A bridge was also placed at the bottom of the 8 1/4" casing (at 864') and cemented with ten (10) sacks of cement.

Witnessed by E. J. Fisher Elmer J. Fisher, Owner
Name Company Title

Subscribed and sworn to before me this 16

day of Nov, 1939

William T. Mahoney
Notary Public

My Commission expires 10-27-43

I hereby swear or affirm that the information given above is true and correct.

Name Elmer J. Fisher

Position Owner

Representing Elmer J. Fisher

Company or Operator

Address 303 South Cornell, Albuquerque, N.M.

Remarks:

Roy Yarbrough
OIL & GAS INSPECTOR
Title

