



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD NOV 5 1959

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

George W. Riley, Inc. State
(Company or Operator) (Lease)
Well No. 1-2, in SE 1/4 of 36 1/4, of Sec. 9, T. 15-S, R. 28-E, NMPM.
Wildcat Pool, Chaves County, Chaves County.
Well is 657.2 feet from East line and 560 feet from South line
of Section 9. If State Land the Oil and Gas Lease No. is
Drilling Commenced December 11, 1958 Drilling was Completed February 5, 1959
Name of Drilling Contractor George W. Riley, Inc.
Address Box 826, Odessa, Texas
Elevation above sea level at Top of Tubing Head 3579.3'. The information given is to be kept confidential until
19

OIL SANDS OR ZONES

No. 1, from 2514 to 2550 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet
No. 2, from to feet
No. 3, from to feet
No. 4, from to feet

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8"	32#	New	225'	Hallib.			
5 1/2"	15.50#	Used	2612	Hallib.		2514-15, 2519-20 2531-50	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8 5/8"	225	25			
7 7/8"	5 1/2"	2612	50			

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidised w/500 gals. acid through perforations. Oil frac with 11,000
gals. through perforations

Result of Production Stimulation

Depth Cleaned Out

RE ID OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 2750 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing Feb. 5, 1959

OIL WELL: The production during the first 24 hours was 17 barrels of liquid of which 82% was oil; 11.0% was emulsion; 18% water; and 0% was sediment. A.P.I. Gravity 31.3

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. 807	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	227	227	No R. turns				
227	490	263	Red Beds, Salt & Anhy				
490	690	200	Red Beds, Anhy & Shale				
690	807	117	Anhy & Pet Ash				
807	1242	435	Anhy				
1242	1945	703	Anhy & Lime				
1945	2584	639	Lime				
2584	2750	166	Dolomite & Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

11-3-59

(Date)

Company or Operator George W. Riley, Inc.

Address Box 826, Odessa, Texas

Name Tom Ray

Position or Title President