Form 9-331a	N. M. O. C. C. Carry .	E' Budget Bureau No. Form Approved,	_
Form 9-331 a (Feb. 1951)	(SUBMIT IN TRIPLICATE)	Land Office	
PPR C DEPAR	UNITED STATES CHT	Lease No.	
MILLE DEPAG	RTMENT OF THE INTERIOR	Unit	
	GEOLOGICAL SURVEY	N WELLS	
·····	I X II		
NOTICE OF INTENTION TO DRILL			1
NOTICE OF INTENTION TO CHANGE PLANS			
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WEI			
NOTICE OF INTENTION TO SHOOT OR ACIDIZE			
NOTICE OF INTENTION TO PULL OR ALTER CASING.	SUPPLEMENTARY WELL HISTO	RY	
NOTICE OF INTENTION TO ABANDON WELL			
(INDICATE ABOVE BY C	HECK MARK NATURE OF REPORT, NOTICE, OR OT		62
USA-Mehurin NM 051623		wber 3	, 19
Well No. 1 is located 660	ft. from $\left\{ \begin{array}{c} \mathbf{X} \\ \mathbf{S} \end{array} \right\}$ line and .660 ft.	from $\left\{ \begin{matrix} \mathbf{F} \\ \mathbf{W} \end{matrix} \right\}$ line of sec	
مشرحه من ده مد	28-e nden		
(14 Sec. and Sec. No.) (Twp.)) (Range) (Meridian)	New Mexico	
indesignated A4 C	(County or Subdivision)	(State or Territory)	
(State names of and expected depths to objective sand ing point	DETAILS OF WORK	casings; indicate mudding	
See Prognosis	and Plats attached.		OCT 6 1962
	RECEIVE		
	OCT 1 0 1963		Ľ.
	OCT 1 0 1963	Ц	100
I understand that this plan of work must receive Company TENNECO CORPORATION	D. C. C. ARTESIA, OFFIC approval in writing by the Geological Survey by BY ITS MANAGING AGENT TENNE	efore operations may be com	menced.
	ARTESIA, OFFIC approval in writing by the Geological Survey by BY ITS MANAGING AGENT TENNS	efore operations may be com	menc e d.
Company TENNECO CORPORATION	ARTESIA, OFFIC	efore operations may be com CO OIL COMPANY Many A	.W.Lang
Company TENNECO CORPORATION I Address Box 307	ARTESIA, OFFIC	efore operations may be com	.W.Lang

GΡ	С	9	۲	49	7	4

TENNECO OIL COMPANY PROGNOSIS TO DRILL AND COMPLETE

Lease: URA-Mehurin IM 051623

District: Hobbs

Well No.: 1

Field: Round

Location: 660' FEL & 660' FEL, Sec. 24, T-15-S, R-28-E, Chaves County, New Mexico Tank - San Andres

Projected Horizon: San Andres

Estimated TD: 3150'

Estimated Elevation: 3710' GL

Drilling, Casing, and Cement:

- 1. Drill 12 1/4" hole to 300'
- 2. Set 8 5/8", 24#, J-55 csg @ 300' w/insert float collar in top of shoe joint. Cmt w/sufficient Incor High Early Portland cmt containing 2% HA-5. Slurry wt should be 14.85#/gal. Pumping time is 1 hr 12 mins. Record the following data:
 - A. Volume of cmt slurry (cubic ft.).
 - B. Brand name of cmt and additives, percent additives used, and sequence of placement.
 - C. Approx temp of cmt slurry when mixed.
 - D. Actual time cmt in place prior to testing csg.
- 3. If float valve holds, release pressure after WOC 4 hrs, nipple up and displace wtr w/air.
- 4. WOC a total of 8 hrs and pressure test csg w/1000 psi for 30 mins and drill out cmt.

NOTE: The weight on the bit should not exceed 20,000#, and rotary speed should not exceed 60 rpm until top of DC is below base of the csg.

- 5. Drill 7 7/8" hole to approx 3150'. Exact TD will be determined by wellsite Exploitation Engineer.
- 6. Set 4 1/2", 9.5#, J-55 csg @ TD. Use an insert float collar and float shoe in string. Cmt w/150 sx of 50-50 Pozmix "S" w/2% gel (slurry wt 15#/gal); and 50 sx reg cmt containing latex (slurry wt 14.5#/gal to 15.1#/gal).

NOTE: Precede cmt w/20 bbls wtr containing a detergent

- 7. If float valve holds, release rig when top plug is down.
- 8. WOC 8 hrs and run temp survey.
- 9. After WOC 18 hrs, RUDDU, run tbg, displace wtr w/oil and pressure test csg w/1500 psi for 30 mins.

Drilling Fluid:

- 1. Drill surface hole w/aerated wtr.
- 2. Drill w/air from base of surface pipe to TD.

Page 2 Prognosis to Drill & Complete USA-Maburin NM 051623 Well No. 1

Drilling Time:

1. Record 1' drlg time from surface to TD w/a geolograph or equivalent recorder.

Drill Pipe Measurements:

1. Tally DP under company supervision at all csg points and at TD.

Samples:

1. Catch 10' samples from 1000' to TD, or as specified by company Exploitation Engineer. Label and tie in bundles of 100'.

Blowout Preventer:

- 1. Double ram w/manual and remote hydraulic or air controls are required. BOP will be tested daily.
- 2. A rotating pack off head is required while drlg w/air.

Hole Deviation:

- 1. Run slope test every 100' on surface hole. Max allowable deviation in surface hole is 1 1/2 degree.
- 2. Run slope test every 500' from base of surface to TD.
- 3. If hole deviation changes more than 1 1/2 degree in any 100' interval, a string reamer will be run to wipe out dog leg.
- 4. If hole deviation changes more than 2 degrees in any 100' interval, the hole will be plugged back and straightened.
- 5. Max allowable hole deviation from base of surface csg to TD is 4 degrees.

Surveys

- 1. Run GR w/formation density log w/detail as required
- 2. Run w/detailed section as required NOTE: Induction log through logging program may be changed at TD

Completion

1. To be determined at TD.

ORIGINAL SIGNED BY, C. W. NANCE

APPROVED:

C. W. Nance ORIGINAL APPROVED: SIGNED BY A. W. LANG

A. W. Lang

	WEL	NEW MEXICO		SERVATION			FORM Revised :
	SEE IN	STRUCTIONS FO	OR COMPLETI	NG THIS FORM	ON THE RE	VERSE SIDE	
Operator			SEC1	TION A			Watt Na
•	OIL COMPANY			A MEHURIN	NM0516	23	Vell No.
Uait Letter	Section	Township		Range	County	······	
P Actual Footage Le	24	15 Sour	H	28 EAST	Сн	AVES	
660	feet from the	SOUTH	line and	66 0 fe	et from the	EAST	line
Ground Level Eler			Pool				Dedicated Acreage:
3710 Ret.	Same	Andres	·	Indesignated	•		
wise? YES	o question one is	If answer is "yes, "no," list all the	," Type of Co	asolidation	terests belo		tization agreement or
		SECTION	8				CERTIFICATION
						in SECTI	certify that the inform ON A above is true a he best of my knowled
						Natio	Pang .
						Position Company	. Production B
						Tente	a Oll Crayery
				1		Date OG	Lober 3, 1962
1	i						
	1	I		•			certify that the well lo
	STATE					shown on plotted fr surveys a supervisi	the plat in SECTION om field notes of actu- ande by me or under m on, and that the same ct to the best of my k
	STATE	OR RVEY				shown on plotted fr surveys n supervisi- and corre	the plat in SECTION om field notes of actu- ande by me or under m on, and that the same ct to the best of my h f.