


N. M. O. C. C. COPY
(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office New Mexico
Lease No. NM-031713
Unit 9



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

APR 9 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Lease No. 205710
G.M. Cone Federal

TEXACO Inc. P.O. Box 728
Hobbs, New Mexico March 6, 1962

Well No. 1 is located 1980 ft. from [S] line and 1980 ft. from [E] line of sec. 23
NW 1/4, SE 1/4 Sec. 23 15-S 29-E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat (Ellenburger) Chaves New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3942 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

TD - 12,166'

- Verbal permission received to plug and abandon, Mr. Jim Knauff, 4:15 p.m. December 7, 1961. Subject well was plugged as follows:
1. Spot 30 sx cement, 11742-11,842'
 2. Spot 30 sx cement, 10,935-11,035'
 3. Spot 30 sx cement, 10,150-10,250'
 4. Spot 30 sx cement, 9,639- 9,739'
 5. Spot 30 sx cement, 8,400- 8,600'
 6. Spot 35 sx cement, 7,445- 7,545'
 7. Spot 35 sx cement, 6,105- 6,205'
 8. Spot 35 sx cement, 3,995- 4,095'
 9. Spot 35 sx cement, 2,838- 2,938'
 10. Install 40 sx cement surface plug, 4" marker extending 4' above ground level. Clean location for inspection as per USGS regulation. Plug and abandon complete 10:30 A.M. December 8, 1961.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company TEXACO Inc.

Address P.O. Box 728

Hobbs, New Mexico

J. G. Blevins, Jr.

By

J. G. Blevins, Jr.
Title Assistant District Superintendent