

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY Artesia, NM 88400

Form Approved
Federal Register No. 41, 17474

c/sf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection well

1. NAME OF OPERATOR

Burk Royalty Co.

2. ADDRESS OF OPERATOR

P. O. Box BRC, Wichita Falls, Texas 76307

4. LOCATION OF WELL (Report location clearly and in accordance with any State rules and regulations.
See also space 17 below.)
At surface

Unit "C", 330' FNL & 1,650' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, RT, GR, etc.)

3906' GR.

O. C. D.

ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.

NM 0306551

6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Double "L" Queen Unit

8. FARM OR LEASE NAME

Double "L" Qn Ut TR 9

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Double "L" Qn Association

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 7-15S-30E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. POSSIBLE CHANGES OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plug & Abandon:

Nov. 9, 1982 - Set easy drill bridging plug at 1950'. Spotted 4 sx gel on top of plug; then spotted 25 sx cement through 2" tubing. (Plug - 182.5'). Spotted 3 sx gel and 25 sx cement at 350' (Plug - 182.5'). Spotted 10 sx cement at surface. The 5 1/2" casing was left in hole.

RECEIVED

NOV 15 1982

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

Post ID-2
2-18-83
P+R

18. I hereby certify that the foregoing is true and correct

SIGNED Fred M. Lynch TITLE Petroleum Engineer

DATE November 12, 1982

(This space for Federal or State Approval)

APPROVED BY PETER W. CHESTER

CONDITIONS OF APPROVAL, IF ANY:

FEB 8 1983

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side