

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or reopened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 320	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 123	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Salt _____ 1230	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 1245	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____ 1305	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ 1921	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qizte _____
T. Glorieta _____	T. McKee _____	T. Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	45	45	Sand & Caliche				
45	70	25	" Shale				
70	105	35	Red Shale				
105	315	210	Red Rock				
315	340	25	Limne				
340	395	55	Anhy				
395	408	13	Shale				
408	435	27	Anhy				
435	445	10	Salt, Red Rock				
445	1095	650	Salt				
1095	1160	65	Anhy, Shale				
1160	1180	15	" Salt				
1180	1190	10	"				
1190	1200	10	Red Shale, Anhy				
1200	1220	20	Anhy				
1220	1270	50	" Shale				
1270	1350	80	Red Shale				
1350	1475	125	" Anhy				
1475	1805	330	Anhy				
1805	1840	35	" Red Shale				
1840	1900	60	Sandy, Shale				
1900	1970	70	Anhy, Red Shale				
1970	1984	14	Anhy, Sandy Limne				
1984	1992	8	Sand + Sandy Shale				
1992	2010	18	Anhy				
2010	2021	11	Anhy, Shale				

RECEIVED

APR 27 1970

OIL CONSERVATION COMM.
HOBBS, N. M.