

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon <u>7485'</u>	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>8025'</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>8365'</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>423'</u>	T. Miss <u>8616'</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>1020'</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg <u>1395'</u>	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>1700'</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Quize _____
T. Glorieta <u>3170'</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>4502'</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>5283'</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>6400'</u>	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) <u>7155'</u>	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	90		Red beds				
90	420		Gypsum & red sand				
420	810		Anhy & Dolo				
810	895		Anhy				
895	1020		Dolo & anhy				
1020	1400		Red sh, red sd, anhy, dolo				
1400	1700		Anhy, sd, dolo				
1700	2290		Anhy & dolo				
2290	2965		Dolo & anhy				
2965	3145		Anhy & dolo				
3145	3300		Sd & anhy				
3300	3570		Dolo, sh & anhy				
3570	3860		Sd, sh & anhy				
3860	4500		Dolo, anhy & sh				
4500	4650		Sd				
4650	4900		Sd, dolo & anhy				
4900	5282		Dolo, anhy, sh				
5282	5660		Red sh, anhy				
5660	6400		Dolo & anhy				
6400	6640		Gray Lm				
6640	7150		Sd, sh & lm				
7150	7480		Lm & gray sh				
7480	8020		Gray sh & lm				
8020	8400		Lm, Red & Gray sh, sd				
8400	TD		Lm, sh & sd				
	<u>8664</u>						