Form 9-331 (May 1963)		D STATES OF THE INTER		CATE* Form approved. Budget Bureau No. 42 5. LEASE DESIGNATION AND SER.
		ICAL SURVEY		NM-0458356
CLIN	IDDY NOTICES A			6. IF INDIAN, ALLOTTEE OR TRIB
	S form for proposals to drill Use "APPLICATION FOR		DN WELLS back to a different reservoir. proposals.)	
1. OIL GAS WELL WELL	OTHER			7. UNIT AGREEMENT NAME
WELL TO WELL. 2. NAME OF OPERATOR	UTHER			8. FARM OR LEASE NAME
Pubco Fe	troleum Corporat	ion		Sulimar Federal
3. ADDRESS OF OPERATIO			· · · · · · · · · · · · · · · · · · ·	9. WELL NO.
Box 869,	Albuquerque, Ne	w Mexico 8710)3	2
4. LOCATION OF WELL (See also space 17 be At surface	Report location clearly and : low.)	in accordance with an;	y State requirements.*	10. FIELD AND FOOL, OR WILDCA Sulimar Queen
990' FNL & 1650' FEL, Sec. 26, T15S, R29E				11. SEC., T., R., M., OR BLK. AND
Chaves County, New Mexico				Sec. 26, T15S, R29
14. PERMIT NO.		ATIONS (Show whether D	DF, RT, GR, etc.)	12. COUNTY OB PARISH 13. STA
		3933 GR.		Chaves New M
16.	Check Appropriate	2 Box To Indicate I	Nature of Notice, Report,	, or Other Data
	NOTICE OF INTENTION TO :		8	UBSEQUENT REPORT OF:
TEST WATER SHUT-	OFF PULL OR AL	TER CASING	WATER SHUT-OFF	X REPAIRING WELL
FRACTURE TREAT	MULTIPLE C	COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZIN	G ABANDONMENT*
REPAIR WELL	CHANGE PLA	ANS	(Other)	Spudding
(Other)			(NOTE: Report a Completion or R	results of multiple completion on Well ecompletion Report and Log form.)
17. DESCRIBE PROPOSED O proposed work. I nent to this work.)				
Spudded 10 Drilled to Set 8-5/8"	" cable tool hol 405'. Top of S 0.D. 20#/ft. H-	e at 3:00 p.m alt 390'. 40 casing at	405, cemented with	
Spudded 10 Drilled to Set 8-5/8"	" cable tool hol 405'. Top of S 0.D. 20#/ft. H-	e at 3:00 p.m alt 390'. 40 casing at	405, cemented with	1 75 sxs 2% CaCl ₂ .
Spudded 10 Drilled to Set 8-5/8"	" cable tool hol 405'. Top of S 0.D. 20#/ft. H-	e at 3:00 p.m alt 390'. 40 casing at	405, cemented with	1 75 sxs 2% CaCl ₂ .
Spudded 10 Drilled to Set 8-5/8"	" cable tool hol 405'. Top of S 0.D. 20#/ft. H-	e at 3:00 p.m alt 390'. 40 casing at	405, cemented with	1 75 sxs 2% CaCl ₂ .
Spudded 10 Drilled to Set 8-5/8" Plug down WOC 24 hrs No show of	" cable tool hol 405'. Top of S 0.D. 20#/ft. H-	e at 3:00 p.m alt 390'. 40 casing at	405, cemented with	1 75 sxs 2% CaCl ₂ .
Spudded 10 Drilled to Set 8-5/8" Plug down WOC 24 hrs No show of	" cable tool hol 405'. Top of S 0.D. 20#/ft. H- 11:00 a.m. 12/3/ ., bailed hole d water or fluids	e at 3:00 p.m alt 390'. 40 casing at 69. ry, drilled p either befor	405, cemented with	1 75 sxs 2% CaCl ₂ .
Spudded 10 Drilled to Set 8-5/8" Plug down WOC 24 hrs No show of 18. I hereby certify that SIGNED	" cable tool hol 405'. Top of S 0.D. 20#/ft. H- 11:00 a.m. 12/3/ ., bailed hole d water or fluids	e at 3:00 p.m alt 390'. 40 casing at 69. ry, drilled p either befor	A. 11/26/69. 405, cemented with lugs. e or after setting 07013	75 sxs 2% CaCl ₂ . casing: E E E I V E DEC 23 1969 DEC 2 DEC 15 DEC15 DEC15 DEC15 IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS
Spudded 10 Drilled to Set 8-5/8" Plug down WOC 24 hrs No show of 18. I hereby certify that SIGNED	" cable tool hol 405'. Top of S 0.D. 20#/ft. H- 11:00 a.m. 12/3/ , bailed hole d water or fluids the foregoing is true and d the foregoing is true and d true and d	e at 3:00 p.m alt 390'. 40 casing at 69. ry, drilled p either befor	A. 11/26/69. 405, cemented with lugs. e or after setting 07013	75 sxs 2% CaCl ₂ . casing: E E E I V E DEC 23 1969 DEC 2 DEC 15 DEC15 DEC15 DEC15 IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS IS
Spudded 10 Drilled to Set 8-5/8" Plug down WOC 24 hrs No show of 18. I hereby certify that SIGNED (This space for Fede APPROVED BY CONDITIONS OF A	" cable tool hol 405'. Top of S. 0.D. 20#/ft. H 11:00 a.m. 12/3/ ., bailed hole d water or fluids the foregoing is true and d the foregoing is true and d the foregoing is true and d tral or State office use) PPROVAL, IF ANY:	e at 3:00 p.m alt 390'. 40 casing at 69. ry, drilled p either befor	A. 11/26/69. 405, cemented with lugs. e or after setting 07013	The formula of the f
Spudded 10 Drilled to Set 8-5/8" Plug down WOC 24 hrs No show of 18. I hereby certify that SIGNED (This space for Fede APPROVED BY CONDITIONS OF A	" cable tool hol 405'. Top of S. 0.D. 20#/ft. H 11:00 a.m. 12/3/ ., bailed hole d water or fluids the foregoing is true and d the foregoing is true and d the foregoing is true and d tral or State office use) PPROVAL, IF ANY:	e at 3:00 p.m alt 390'. 40 casing at 69. ry, drilled p either befor	A. 11/26/69. 405, cemented with lugs. e or after setting DTD13 DTD13 Drilling Engineer	The formula of the f
Spudded 10 Drilled to Set 8-5/8" Plug down WOC 24 hrs No show of 18. I hereby certify that SIGNED (This space for Fede APPROVED BY	" cable tool hol 405'. Top of S. 0.D. 20#/ft. H 11:00 a.m. 12/3/ ., bailed hole d water or fluids the foregoing is true and d the foregoing is true and d the foregoing is true and d tral or State office use) PPROVAL, IF ANY:	e at 3:00 p.m alt 390'. 40 casing at 69. ry, drilled p either befor	A. 11/26/69. 405, cemented with lugs. e or after setting 07013	The formula of the f