

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

### Northwestern New Mexico

T. Anhy _____	T. Canyon <u>7331'</u>	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>7872'</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>8226'</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>1590'</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>2610'</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>4350'</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. <del>Abq</del> Leonard <u>5134'</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>5540'</u>	T. _____	T. Chinle _____	T. _____
T. Penn. <u>6242'</u>	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) <u>6996'</u>	T. _____	T. Penn. "A" _____	T. _____

### FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1050		Anhy, Rd shale & Dol				DST #1 8346' - 8445'
1050	1600		Rd sand, Rd shale, Anhy				Open 1 hr & 15 min no GTS
1600	2600		Dol, Anhy				rec 150' mud.
2600	2800		Sand & Anhy				
2800	4350		Anhy, Dol & Shale				DST #2 8344' - 8480'
4350	4500		Sand & Anhy				Open 1½ hrs, rec 680' mud
4500	5100		Dol & Anhy				& mud cut condensate.
5100	5550		Rd shale & Anhy				Flowing @ rate of
5550	6250		Dol & Anhy				5,750,000 CFDP.
6250	7000		Limestone & gray shale				
7000	7330		Gray Shale & Limestone				
7330	7850		Gray Limestone & gray shale				
7850	8200		Lime & Gray shale				
8200	8550		Blk shale, Ls & sand				
8550	8590		Brown ls & gray shale				