

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI. CATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-04933/0A-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Snyder Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Sulmar Queen *Under*11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 26-155-29E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Cities Service Oil Company ✓

3. ADDRESS OF OPERATOR

Box 69 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1650' FML and 990 FEL of

Sec. 26-T155-R29E, Chaves County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3926 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing Test & Completion ☒  
(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.) Data

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

T.D. 2005 Anhy. and Dolo. PSTD 1994 Well complete. Ran 61 3/4 jts. (1995') 5 1/2" OD 14# J-55 ST&C casing set @ 2004 and cemented w/135 sacks Class C cement w/3# salt and 3# sand per sack. Plug down @ 11:40 AM on 3-22-70. Ran temp. survey. Top of cement @ 1390. WOC 24 hrs. Tested 5 1/2" casing w/600 PSI for 30 min with no drop in pressure. BO to 1994. Perforated 20/holes 1973-1982. Swabbed well dry. Acidized perfs. (1973-1982) w/500 gals. 15% mud acid. Max. press. 1500 PSI, Min. press. 1000 PSI, treated @ 3.4 B/M @ 1500 PSI, ISIP 900 PSI, 5 min. SIP vacuum. Swabbed part of load water and swabbed dry. Water fraced down 5 1/2" csg. w/17000 gals. gelled salt water w/15000# 20-40 sand and 5000# 10-20 sand. Max. press. 1700 PSI, min. press. 1000 PSI treated @ 32.7 B/M. ISIP 1350 PSI, 10 min. SIP, 1300 PSI, 1 1/2 hr. SIP 1300 PSI. Ran 2 3/8" OD EUE tubing set @ 1940 w/packer set @ 1902. Swabbed on potential 25 BO + 24 BLW/10 hrs. Grav. 36.6 for a rated 24 hr. potential of 228 BO + 58 BW.

RECEIVED

APR 10 1970

RECEIVED  
APR 3 - 1970  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

B. B. L.  
ARTESIA, OFFICE

District Admin. Supervisor

DATE

April 6, 1970

(This space for Federal or State use only)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD PURPOSES

APR 9 - 1970

Date

ACTING

District Engineer

\*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.