

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____ T. Canyon 7371
T. Salt _____ T. Strawn 7902
B. Salt _____ T. Atoka 8278
T. Yates _____ T. Miss 8606
T. 7 Rivers _____ T. Devonian _____
T. Queen 960 T. Silurian _____
T. Grayburg _____ T. Montoya _____
T. San Andres 1611 T. Simpson _____
T. Glorieta 2661 T. McKee _____
T. Paddock _____ T. Ellenburger _____
T. Blinbry _____ T. Gr. Wash _____
T. Tubb 4386 T. Granite _____
T. Drinkard _____ T. Delaware Sand _____
T. Abo 5166 T. Bone Springs _____
T. Wolfcamp 6282 T. _____
T. Penn. _____ T. _____
T. Cisco (Bough C) 7040 T. _____

Northwestern New Mexico

T. Ojo Alamo _____ T. Penn. "B" _____
T. Kirtland-Fruitland _____ T. Penn. "C" _____
T. Pictured Cliffs _____ T. Penn. "D" _____
T. Cliff House _____ T. Leadville _____
T. Menefee _____ T. Madison _____
T. Point Lookout _____ T. Elbert _____
T. Mancos _____ T. McCracken _____
T. Gallup _____ T. Ignacio Qtzte _____
Base Greenhorn _____ T. Granite _____
T. Dakota _____ T. _____
T. Morrison _____ T. _____
T. Todilto _____ T. _____
T. Entrada _____ T. _____
T. Wingate _____ T. _____
T. Chinle _____ T. _____
T. Permian _____ T. _____
T. Penn. "A" _____ T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	950		Red sh & anhy				DST #1 8275' - 8414'
950	1600		Anhy, sd, rd sh				SFP 1600# - 1/2" choke
1600	2650		Dolo & anhy				Rec 35 cc gas, 300 cc
2650	4380		Anhy, yellow & rd sh, dolo & sd				condensate & gas
4380	4700		sand & anhy				
4700	5150		Anhy, Dolo				
5150	5580		Red & Gr sh, anhy				
5580	6330		Dolo, anhy, red sh				
6330	7100		Limestone, gr sh				
7100	7900		Limestone, rd & gr sh				