

UNITED STATES OF AMERICA
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYBUDGET CATEGORY
(Other instructions
reverse side)Form approved,
Budget Bureau No. 42

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry		5. LEASE DESIGNATION AND SERIAL NO. NM 0555291	
2. NAME OF OPERATOR McGrath & Smith, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 418 Bldg. of the Southwest, Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL and 1980' FWL		8. FARM OR LEASE NAME Keeler Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 3695 KB 3706		10. FIELD AND POOL, OR WILDCAT Wildcat	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17, T-14-S, R-29-E	
		12. COUNTY OR PARISH Chaves	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input checked="" type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
(Other) <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
(Other) <input type="checkbox"/>	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 4:15 p.m. 9-13-70. Drld 11" hole to 251'. Cmtd 8 5/8-24# Csg at 251' with 150 sx. Circ 25 sx. WOC 18 hrs. Tested 8 5/8 to 300 psi for 30 min. - o.k. Drilled 7 7/8 hole to TD 2245. Reached TD at 5:00 p.m. 9-16-70. Ran GR Acoustic, LL, ML Logs. Cored Queen 1600-1632'. Rec. 32' NS, decided to P&A as follows:

Spot cement plugs as follows:

30 sx	1560-1660	Queen
30 sx	675- 775	B. Salt
30 sx	200- 300	B. 8 5/8
10 sx	Top 8 5/8 from 0-10'	

Install DHM and cap on 8 5/8". P&A will be done 9-17-70

Telephone approval of above procedure from Jim Knauf on 9-17-70.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim KnaufTITLE SuperintendentDATE September 17, 1970

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
SEP 1970
R. L. BEEKMA
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side