

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____ 7413	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____ 7958	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____ 8370	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____ 8685	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 1667	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 2680	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 4410	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 5198	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 6320	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____ 7089	T. _____	T. Penn. "A" _____	T. _____
Slaughter - 2110	Lower Cherokee Lime - 8062		
L/Leonard - 5627	FORMATION RECORD (Attach additional sheets if necessary)		

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	350		Anhy, Sand & Red Shale				
350	900		Anhy & Red Shale				
900	1350		Red Sand, Shale & Anhy				
1350	1650		Anhy, Dolo & Red Shale				
1650	2100		Gray Dolo & Anhy				
2100	2550		Brown Dolo				
2550	2680		Limestone				
2680	3500		Anhy & Dolo				
3500	4400		Dolo, Anhy & Red Shale				
4400	4550		Sand & Anhy				
4550	5200		Dolo & Anhy				
5200	5600		Red Shale & Anhy				
5600	6300		Dolo & Anhy				
6300	7100		Limestone & gr & rd sh				
7100	7400		Limestone & Shale				
7400	7650		Limestone				
7650	8050		Gr Shale & Limestone				
8050	8350		Lime, Shale & Sand				
8350	8700		Sand & Lime				
8700	8790		Shale & Lime				