

COUNTY CHAVES FIELD Buffalo Valley STATE NM 30-005-60155
MAP
OPR READ & STEVENS

1 Trobaugh "A" State Com
Sec 12, T-15-S, R-27-E
1650' FSL, 1650' FEL of Sec
Spd 12-13-70

CO-ORD

CLASS

EL

FORMATION

DATUM

FORMATION

DATUM

C&G & SX - TUBING

12 3/4" at 349' w/200 sx
8 5/8" at 1720' w/200 sx
4 1/2" at 8709' w/300 sx.

LOGS EL GR RA IND HC A

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Sealing Service, Inc.

CONT. WEK

F.R. 12-8-70

PROP DEPTH 8800'

TYPE RT

(Atoka)

AMEND OPERATOR, Formerly reported as Reed &

Stevens

12-14-70

Drilg. 675' 1m

12-21-70

Drilg. 6530' 1m

1-4-71

Drilg. 7360' 1m

1-12-71

Drilg. 8360'

1-13-71

TD 8597'; Prep Drill

1-25-71

Cored 8480-8521', rec 32', no descr

Cored 8521-8556', rec 25', no descr

DST 8270-8556', open 3 hrs 30 mins, CTS 9 mins

Flwd gas @ 4250 MCF/GPD & dec to 2800 MCF/GPD

thru 3/4" chk in 2 hrs, Flwd @ 1250 MCF/GPD thru

18/64" chk in 30 mins, SFP 700#, rec 430' cond

+ 50' cond CM, 1 hr ISIP 3167#, FP 712-1459#,

2 hr FSIP 3075#, HP 3970-3947#

Cored 8581-97', no recovery, bbl stuck

TD 8790'; WOC

DST 8572-8615', Pkrs failed

DST 8545-8615', Pkrs failed

DST 8695-8790', open 1 hr, rec 30' DM, 30 min

ISIP 163#, FP 93-116#, 1 hr FSIP 186#

2-2-71

CHAVES Buffalo Valley NM Sec 12, T15S, R27E
READ & STEVENS 1 Trobaugh "A" State Com Page #2

2-8-71

TD 8790'; PBD 8656'; Prep Perf

Spotted 200 gals acid

Perf 8516-20', 8526-33', 8558-62' w/2 SPF

TD 8790'; PBD 8656'; Tstg

Perf 8581-93' w/2 SPF

Flwd @ 950 MCF/GPD thru 5/8" chk, TP 92-87#

(8516-93')

Pkr @ 8573'

Swbd Dry (8581-93')

Att Acid (8581-93') failed to break

Re-Perf 8581-93' w/2 SPF

Pkr @ 8573'

Att Acid (8581-93') had communications

Pkr @ 8542'

Acid (8558-93') 250 gals (MCA)

Swbd Dry (8558-93')

Flwd gas @ 10 MCF/GPD (8558-93')

TD 8790'; PBD 8656'; Tstg

Acid (8558-93') 2000 gals

Flwd 380 MCF/GPD thru 3/8" chk, TP 105# (8558-93')

TD 8790'; PBD 8656'; SI

SITP 1924#

TD 8790'; PBD 8656'; Prep Test

Perf @ 8582', 8585', 8587'

TD 8790'; PBD 8656'; SI PBU

Flwd gas @ TSTW (8581-93')

Perf 8624-30', 8639-45' w/2 SPF

Flwd gas @ 1600 MCF/GPD thru 1/2" chk, TP 240#

(8516-8645')

TD 8790'; PBD 8656'; SI

Flwd 1550 MCF/GPD thru 1/2" chk, TP 225#

(8516-8645')

TD 8790'; PBD 8656'; Tstg

Flwd 1250 MCF/GPD thru 1/2" chk, TP 175#

(8516-8645')

TD 8790' PBD 8656' w/o perf.

Flwd 1250 MCF/GPD, 1/2" chk, TP 175# (8516-8645')

4-19-71 TD 8790' PBD 8656' w/o perf.