

NO. COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	1
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

DEC 7 1970

O. C. C.

ARTESIA OFFICE

Form C-101  
Revised 1-1-65

5A. Indicate Type of Lease
STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
5. State Oil & Gas Lease No.
K-6798, K-2431

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>		-	
b. Type of Well		8. Firm or Lease Name State	
OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		Trobaugh "A" Com	
c. Name of Operator		9. Well No.	
Read & Stevens		1	
d. Address of Operator		10. Field and Pool, or Wildcat	
P.O. Box 2126, Roswell, New Mexico 88201		Buffalo Valley Penn	
4. Location of Well		12. County	
UNIT LETTER J LOCATED 1650 FEET FROM THE East LINE		Chaves	
AND 1650 FEET FROM THE South LINE OF SEC. 12 TWP. 15S RGE. 27E NMPM			
19. Proposed Depth		19A. Formation	
8800'		Atoka	
20. Rotary or C.T.		Rotary	
21. Elevations (Show whether DF, RT, etc.)		21B. Drilling Contractor	
3570.4		WEK Drilling Company	
21A. Kind & Status Plug. Bond		22. Approx. Date Work will start	
Statewide		December 7, 1970	

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/2"	12 3/4"	34#	330'	350	Cir to Surface
11"	8 5/8"	24#	1600'	200	T. Slaughter
7 7/8"	4 1/2"	10.5#, 11.6#	8800'	350	7100'

APPROVAL VALID  
FOR 90 DAYS UNLESS  
DRILLING COMMENCED,  
EXPIRES 3-7-71

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Michael A. Hume Title \_\_\_\_\_ Date 12-4-70

(This space for State Use)

APPROVED BY W. A. Gressitt TITLE OIL AND GAS INSPECTION DATE DEC 7 1970

CONDITIONS OF APPROVAL, IF ANY:

use adequate blowout preventer

Cement must be circulated to  
surface behind 12 3/4" casing