

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N M. Oil Cons. Division
8 . . S. 1st Street
Artesia, NM 88210-2834

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NM-0390243

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Saga Petroleum, LLC

3. Address and Telephone No.

415 W. Wall, Suite 1900, Midland, TX 79701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 1650' FEL

Sec. 12, T-15-S, R-29-E Unit Letter B

7. If Unit or CA, Agreement Designation
Double L Queen Unit
Agreement NMNM070934A

8. Well Name and No.

Double L Queen Tract 11 #1

9. API Well No.

30-005-60162

10. Field and Pool, or Exploratory Area
Double L Queen

11. County or Parish, State

Chaves, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-04-01 Set 5-1/2" CIBP @ 1930', cap w/ 35' cmt. w/ dump bailer.

4-05-01 Mix mud & circulate hole.

4-05-01 Perf 4 holes @ 1300', tag plug @ 1124'.

4-05-01 Perf 4 holes @ 417', set pkr @ 60', sqz. 35 sx cmt.

4-06-01 Tag plug @ 277'.

4-06-01 Perf @ 50', circulate cmt. from 50' to surface out of 8-5/8" csg. Leave 5-1/2" full of cmt.

4-06-01 Install dry hole marker.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.



14. I hereby certify that the foregoing is true and correct

Signed David R. Glass
(This space for Federal or State office use)

Title Agent

Date 4-11-01

Approved by (ORIG: SGD.) DAVID R. GLASS
Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date APR 20 2001

RECEIVED

APR 16 '01

BLM
ROSENBL, NM