

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

DEC 1 1971

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELL C. C.

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator ROARK & HOOKER	5. State Oil & Gas Lease No. K-6772
3. Address of Operator P. O. Box 2708, Abilene, Texas 79604	7. Unit Agreement Name
4. Location of Well UNIT LETTER L 330 FEET FROM THE West LINE AND 1650 FEET FROM South 24 14-S 20-E THE LINE, SECTION TOWNSHIP RANGE NMPM.	8. Farm or Lease Name Sun - State
	9. Well No. 1
	10. Field and Pool, or Wildcat Double "L" (Queen)
	12. County Chaves
15. Elevation (Show whether DF, RT, GR, etc.) 3795 GR	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/> (surface)	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well was spudded with cable tools at 12:00 noon October 28, 1971. On October 30, 1971, 305 ft. of new 8-5/8" 24# J-55 casing was set at 305 ft. and cemented with 100 sacks of 2% HA-S cement. Plug down at 6:00 PM October 30. Cement circulated. WOC 20 hours. Drilled 20 ft. of cement in pipe. Drilled out the bottom of shoe. Bailed dry. Let set for 2 hours. Run bailer. Hole still dry. Started drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *J. P. Mitchell*

TITLE

Production Superintendent

DATE

Nov. 29, 1971

APPROVED BY *W. A. Gressett*

TITLE

OIL AND GAS INSPECTOR

DATE

DEC 1 1971

CONDITIONS OF APPROVAL, IF ANY: