

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO.	
2. NAME OF OPERATOR Yates Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, New Mexico 88210		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FML & 330' FEL of Sec. 34-15S-29E		8. FARM OR LEASE NAME Federal "CU"	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3836' GR		10. FIELD AND POOL, OR WILDCAT Sullivan Queen	
		11. SEC. T., R., M., OR BLE. AND SURVEY OR AREA Sec. 34-15S-29E Unit A 1MPM	
		12. COUNTY OR PARISH Chaves	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set. 5½" & 7" Prod. Csg

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-30-72 - TD 1908'. Ran a tapered string of production casing as follows: Ran 348' of 5½" 15.5#, J-55 and 1552' of 7" 20 and 23# J-55 casing (Total 1900') and 1 guide shoe set at 1908'. Centralizers at 1874' and 1842'. Cemented with 125 sacks of Incor Heat. P.D. at 10:00 PM 3-30-72. WOC 24 hours and tested casing to 1000#. Tested OK.

Perforated w/1 shot per foot as follows: 1871½, 1872, 1872½, 1873, 1873½, 1874, 1875, 1875½, 1876, 1877, 1878, 1879, 1880, 1880½, 1881½, 1882, 1883, 1884, & 1886½.

Sand Frac'd using 250 gallons of acid, 10000# 20-40, 5000# 10-20 sand and 500 barrels of crude oil.

RECEIVED
APR 13 1972
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

4-13-72

(This space for Federal or State office use)

TITLE

DATE

APPROVED
APR 13 1972
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side