

RECEIVED  
ARTESIA, N.M. 88001

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

OCT 13 1987

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Robert N. Enfield

3. ADDRESS OF OPERATOR

P.O. Box 2431, Santa Fe, NM 87501

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FNL & 990' FEL of Sec. 11

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

NM-0304758-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 1-11

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Buffalo Valley Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11, T15S, R27E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3533.2 KB 3522. GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/18/84 Pump 30 bbls. brine down tubing. Circulate 50 bbls brine mud. Spot at 8260'. Set CIBP at 8350', set 35' cement plug on top.

4/19/84 Shot 4-1/2" casing at 6400'. Recovered 6400'. Put 60 sack cement plug 75' in to stub. Plud down. *Proc*

4/20/84 Tag plug at 6350'. Pump 150 bbls mud to spot (brine w/40 sx gel). Spot 75 sx plug at 1797' in and out of 8-5/8" csng w/2% CACL2. Pumped 125 bbls mud brine w/35 sks gel. WOC. Went in hole with wireline. Tag plug at 1601', cemented with 50 sxs. *75 sx plug 4317'*

4/21/84 Cut off well head, set 15 sx plug in top of casing. Weld plate on top of casing. Installed dry hole marker. Cut off anchors, break out cellar boards. Fenced pits. Subsurface Safety Valve, Man, and Type. Set @ *Port IO-2 7-20-84*

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert N. Enfield

TITLE Operator

DATE 6/25/84

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

\*See Instructions on Reverse Side

APPROVED  
PETER W. CHESTER

OCT 6 1987

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA