

ROS 100 COPY

Form 9-321
May 1963

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on the
reverse side)

Form Approved
Hodget Series No. 43-11424
CASE ORIGINATOR AND SERIAL NO.

BM 16114

WELL OR OTHER IDENTIFICATION NUMBER

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir
See APPLICATION FOR PERMIT for such proposals.)

1. OIL ☐ GAS ☒ WELL ☐ OTHER ☐	2. NAME OF OPERATOR WOOD & COCKBURN, INC.	3. ADDRESS OF OPERATOR 511 West Ohio, Midland, Texas 79701	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) Unit letter P Located 560' from the East Line and and 510' from the South Line of Section 3	5. ELEVATIONS (Show whether DF, HT, OR, etc.) 3852' G. L.	6. FIELD AND PROD. OR SURVEY Prod. Double L. Juan Assoc.	7. SEC. T. R. N. OF R. AND SUBST. OR AREA Sec. 3, T15S, R29E	8. COUNTY OR PARISH OR STATE Chaves New Mexico
15. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data							
NOTICE OF INTENTION TO				SUBSEQUENT REPORT OF			
TEST WATER ABST. OFF.	DRILL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL				
FRAC. TREAT.	MULTIPLE COMPLETE	FRAC. TREATMENT	EXTENDING CASING				
SHOULDER ACIDIZING	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*				
REPAIR WELL	CHANGE PLANS	(Other: 8 5/8" and 4 1/2" casing)					
(Other:)				(Note: Report results of multiple completion on Well Completion or Recumpletion Report and Log form.)			
17. OIL RISE, RIVINER, OR SPRING OR OTHER SOURCE (If any state all pertinent details and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)							

An 11" hole was drilled to 243' and 8 5/8" 24#/ft. casing run and cemented with 100 sacks. A 7 7/8" hole was then drilled to 1960' and 4 1/2" 9.5#/ft. casing was run to TD and cemented with 200 sacks. None was pulled.

The 4 1/2" casing was perforated from 1842' - 1852' with seven (7) holes and fractured with 20,000 gal. water and 24,000# sand.

RECEIVED

U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE **Vice President, Production** DATE **March 21, 1974**

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITION OF APPROVAL IF ANY:

