Copy to SF

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [ ] GAS WELL [X] OTHER

2. NAME OF OPERATOR: WOOD & COCKBURN, INC.

3. ADDRESS OF OPERATOR: 511 West Ohio, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface

Unit letter P located 660' from the East line and 510' from the South Line of Section 3.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 3892' GL

5. LEASE DESIGNATION AND SERIAL NO.: NM 16114

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: Federal "B"

9. WELL NO.: 1

10. FIELD AND POOL, OR WILDCAT: Und. Double L Queen Assoc.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec. 3, T-15-S, R-29-E

12. COUNTY OR PARISH: Chaves

13. STATE: New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON* X	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other)	
(Other)		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The surface casing (8 5/8") is set @ 243' and cemented with 100 sx (Cmt. circ.). The production casing (5 1/2") is set @ 1960' and cemented w/200 sx. We plan to pull 1100' of 5 1/2" casing and spot a 30 sx cmt. plug from 1050' to 1150'. Another 30 sx plug will be spotted from 193' to 293'. A 5 sx plug will be spotted at the surface. A plate welded onto the 8 5/8" casing and a steel marker installed. A 9.[illegible] mud will be used in spotting cement plugs. The planned date [illegible] operations will be October 1, 1974

ILLEGIBLE

RECEIVED
AUG 14 1974
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED R. K. Bo[illegible] TITLE Vice Pres. Production DATE August 13, 1974

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side