D STATES SUBMIT IN TRIP: TE* (Other lustructions of re-UN'TED STATES

Form approved. Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY			5. LEASE DESIGNATION AND SERIAL NO. NM-0493370	
SUNDRY (Do not use this form f	NOTICES AND REPORTS for proposals to drill or to deepen or plug "APPLICATION FOR PERMIT—" for such	ON WELLS back to a different reservoir Proposals ECEIVE	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
1. OIL V GAS			7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR	OTHER	JUL 1 1976	S. FARM OR LEASE NAME	
McClellan Oil	CORPORATION		FEDERAL "7"	
3. ADDRESS OF OPERATOR	SON, ORALL TON	O. C. C.	9. WELL NO.	
	Roswell, New Mexico		1	
See also space 17 below.)	location clearly and in accordance with an	y State requirements.*	10. FIELD AND POOL, OR WILDCAT	
At surface			WILDCAT	
660' FS & EL			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
			SEC. 7-T15S-R30E	
14. PERMIT NO.	15. ELEVATIONS (Show whether D	OF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE	
			CHAVES NEW MEXICO	
16. CF	neck Appropriate Box To Indicate I	Nature of Notice, Report, or O	ther Data	
NOTICE	OF INTENTION TO:	SUBSEQUE	ONT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT* X	
REPAIR WELL (Other)	CHANGE PLANS	(Other) (Note: Report results of	of multiple completion on Well	
	LETED OPERATIONS (Clearly state all pertine is directionally drilled, give subsurface local		tion Report and Log form.) ucluding estimated date of starting any depths for all markers and zones perti-	
RECEIVED VERBA	L APPROVAL TO ABANDON	N FEBRUARY 10, 1974	•	
FILLED HOLE WI	TH HEAVY MUD. SPOTTE	D CEMENT PLUGS TOT	al depth to 3056',	
1680' то 1580'	(OVER QUEEN SAND), 8	315' to 715' (Base	Salt), 250' to 150'	
(TOP SALT), AN	d 100' to surface. E	RECTED PIPE TYPE D	RY HOLE MARKER.	
			*	
		-04	EIVED	
		REU.	- 71	
			28 1974 PL	
		FED	SURVEY 1	
		u S. GEOL	OGICAL SURVEY NEW MEXICO	

ARTESIA, NE

AGENT	DATE 2/27/74
	DATE
	ACENT

*See Instructions on Reverse Side