

4SF

RECEIVED BY

JUL 16 1985

O. C. D.
ARTESIA, OFFICE

Artesia, NM 88210

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

REC'D

JUL 1 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR
DEPCO, INC. ✓3. ADDRESS OF OPERATOR
800 Central, Odessa, Texas 797614. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FSL & 990' FEL, Sec 25, T-15s,
AT TOP PROD. INTERVAL: R-27e
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)☐
☐
☐
☐
☐
☐
☐
☐5. LEASE (T.M.-O.)
29-115465A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Toles Federal9. WELL NO.
110. FIELD OR WILDCAT NAME
Buffalo Valley (Penn)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 25, T-15-S, R-27-E

12. COUNTY OR PARISH 13. STATE

Chaves

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3600 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We plan to plug this well as follows:

1. Set a retainer @ 8880' & sqz perms from 8930' to 8938' w/50 sxs cmt leaving cmt on top of ret.
2. Spot 100' plug from 5700' to 5600'. Spot 100' plug from 3600' to 3500'. Spot 100' plug from 1925' to 1825'. * Spot 50' plug @ Sfs w/dry hole marker. 9.5# mud laden fluid will be placed between plugs.

* additional plug 375'-275'.

note: all plugs will be in the 4 1/2" casing & the 4 1/2" casing annulus. Tag the plug at 1925'-1825'.
Peter W. Chester

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. Denney R. L. Denney TITLE Chief Prod Clerk DATE 7-8-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
PETER W. CHESTER

JUL 12 1985

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side