

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

OCT 13 '87

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.

ARTESIA, OFFICE

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
DEPCO, INC.

3. ADDRESS OF OPERATOR

800 Central, Odessa, Texas 79761

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1650' FSL & 990' FEL, Sec 25,
AT SURFACE:
AT TOP PROD. INTERVAL: T-15s, R-27e
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-15-85: Perf csg @ 5700', 3600', 1925' & 375'. Set retainer @ 8877' & pmpd 50 sxs cmt thru perfs @ 8930-38' leaving 60' cmt on top of ret. Set ret @ 5595' & pmpd 40 sxs cmt thru perfs @ 5700' leaving 60' cmt on top of ret. Set ret @ 3490' & pmpd 40 sxs cmt thru perfs @ 3600' w/60' cmt on top of ret. Set ret @ 1825' & pmpd 40 sxs cmt thru perfs @ 1925' w/60' cmt on top of ret. Pmpd 50 sxs cmt thru perfs @ 375'. Spotted 50' plug @ sfs. 9.5# mud used between all plugs.

8-29-85: Set dry hole marker & commenced clean-up per stipulations.

Post ID-2
12-13-85
PYA

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. Denney R. L. Denney, Chief Prod Clerk DATE 9-11-85

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

TITLE APPROVED
PETER W. CHESTER

OCT 6 1987

*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA